

CIS Microsoft 365 Foundations Benchmark

v1.0.0 - 12-19-2018

Terms of Use

Please see the below link for our current terms of use:

<https://www.cisecurity.org/cis-securesuite/cis-securesuite-membership-terms-of-use/>

Table of Contents

Terms of Use	1
Overview	6
Intended Audience	6
Consensus Guidance.....	6
Typographical Conventions	7
Scoring Information	7
Profile Definitions	8
Acknowledgements	9
Recommendations	10
1 Account / Authentication	10
1.1 (L1) Ensure multifactor authentication is enabled for all users in administrative roles (Scored)	10
1.2 (L2) Ensure multifactor authentication is enabled for all users in all roles (Scored)	13
1.3 (L1) Ensure that between two and four global admins are designated (Scored)	15
1.4 (L1) Ensure self-service password reset is enabled (Scored).....	17
1.5 (L1) Ensure modern authentication for Exchange Online is enabled (Scored)	19
1.6 (L1) Ensure modern authentication for SharePoint applications is required (Scored)	21
1.7 (L1) Ensure modern authentication for Skype for Business Online is enabled (Scored)	23
1.8 (L1) Ensure that Office 365 Passwords Are Not Set to Expire (Scored)	25
2 Application Permissions	27
2.1 (L2) Ensure third party integrated applications are not allowed (Scored)	27
2.2 (L2) Ensure calendar details sharing with external users is disabled (Scored)	29
2.3 (L2) Ensure O365 ATP SafeLinks for Office Applications is Enabled (Scored)	31

2.4 (L2) Ensure Office 365 ATP for SharePoint, OneDrive, and Microsoft Teams is Enabled (Scored).....	33
3 Data Management.....	35
3.1 (L2) Ensure the customer lockbox feature is enabled (Scored).....	35
3.2 (L2) Ensure SharePoint Online data classification policies are set up and used (Not Scored)	37
3.3 (L2) Ensure external domains are not allowed in Skype or Teams (Not Scored)	38
3.4 (L1) Ensure DLP policies are enabled (Scored).....	40
3.5 (L2) Ensure that external users cannot share files, folders, and sites they do not own (Scored).....	42
3.6 (L2) Ensure external file sharing in Teams is enabled for only approved cloud storage services (Not Scored)	44
4 Email Security / Exchange Online.....	46
4.1 (L1) Ensure the Common Attachment Types Filter is enabled (Scored).....	46
4.2 (L1) Ensure Exchange Online Spam Policies are set correctly (Scored).....	48
4.3 (L1) Ensure mail transport rules do not forward email to external domains (Scored)	50
4.4 (L1) Ensure mail transport rules do not whitelist specific domains (Scored)	52
4.5 (L2) Ensure the Client Rules Forwarding Block is enabled (Scored).....	54
4.6 (L2) Ensure the Advanced Threat Protection Safe Links policy is enabled (Scored)	56
4.7 (L2) Ensure the Advanced Threat Protection Safe Attachments policy is enabled (Scored)	59
4.8 (L2) Ensure basic authentication for Exchange Online is disabled (Scored) ...	61
4.9 (L1) Ensure that an anti-phishing policy has been created (Scored).....	64
4.10 (L1) Ensure that DKIM is enabled for all Exchange Online Domains (Scored)	66
4.11 (L1) Ensure that SPF records are published for all Exchange Domains (Not Scored)	68
4.12 (L1) Ensure DMARC Records for all Exchange Online domains are published (Not Scored)	70

4.13 (L1) Ensure notifications for internal users sending malware is Enabled (Scored)	72
5 Auditing.....	74
5.1 (L1) Ensure Microsoft 365 audit log search is Enabled (Scored)	74
5.2 (L1) Ensure mailbox auditing for all users is Enabled (Scored)	76
5.3 (L1) Ensure the Azure AD 'Risky sign-ins' report is reviewed at least weekly (Not Scored)	78
5.4 (L2) Ensure the Application Usage report is reviewed at least weekly (Not Scored)	80
5.5 (L1) Ensure the self-service password reset activity report is reviewed at least weekly (Not Scored)	81
5.6 (L1) Ensure user role group changes are reviewed at least weekly (Not Scored)	82
5.7 (L1) Ensure mail forwarding rules are reviewed at least weekly (Not Scored)	84
5.8 (L1) Ensure the Mailbox Access by Non-Owners Report is reviewed at least biweekly (Not Scored)	86
5.9 (L1) Ensure the Malware Detections report is reviewed at least weekly (Not Scored)	87
5.10 (L1) Ensure the Account Provisioning Activity report is reviewed at least weekly (Not Scored)	88
5.11 (L1) Ensure non-global administrator role group assignments are reviewed at least weekly (Not Scored)	90
5.12 (L1) Ensure the spoofed domains report is review weekly (Not Scored)	91
5.13 (L2) Ensure Microsoft 365 Cloud App Security is Enabled (Not Scored)	92
5.14 (L1) Ensure the report of users who have had their email privileges restricted due to spamming is reviewed (Not Scored)	94
6 Storage.....	95
6.1 (L2) Ensure document sharing is being controlled by domains with whitelist or blacklist (Scored)	95
6.2 (L1) Ensure expiration time for external sharing links is set (Scored)	97
7 Mobile Device Management	99
7.1 (L1) Ensure mobile device management polices are set to require advanced security configurations to protect from basic internet attacks (Scored)	99

7.2 (L1) Ensure that mobile device password reuse is prohibited (Scored).....	101
7.3 (L1) Ensure that mobile devices are set to never expire passwords (Scored)	103
7.4 (L1) Ensure that users cannot connect from devices that are jail broken or rooted (Scored).....	105
7.5 (L2) Ensure mobile devices are set to wipe on multiple sign-in failures to prevent brute force compromise (Scored)	107
7.6 (L1) Ensure that mobile devices require a complex password to prevent brute force attacks (Scored)	109
7.7 (L1) Ensure that settings are enable to lock multiple devices after a period of inactivity to prevent unauthorized access (Scored).....	111
7.8 (L1) Ensure that mobile device encryption is enabled to prevent unauthorized access to mobile data (Scored)	113
7.9 (L1) Ensure that mobile devices require complex passwords to prevent brute force attacks (Scored)	115
7.10 (L1) Ensure that mobile devices require complex passwords to prevent brute force attacks (Scored)	117
7.11 (L1) Ensure that devices connecting have AV and a local firewall enabled (Scored)	119
7.12 (L1) Ensure mobile device management policies are required for email profiles (Scored).....	120
7.13 (L1) Ensure mobile devices require the use of a password (Scored).....	122
Appendix: Summary Table	124

Overview

This document, Security Configuration Benchmark for Microsoft 365, provides prescriptive guidance for establishing a secure configuration posture for Microsoft 365 running on any OS. This guide was tested against Microsoft 365, and includes recommendations for Exchange Online, SharePoint Online, OneDrive for Business, Skype/Teams, Azure Active Directory, and inTune. To obtain the latest version of this guide, please visit <http://cisecurity.org>. If you have questions, comments, or have identified ways to improve this guide, please write us at feedback@cisecurity.org.

Intended Audience

This benchmark is intended for system and application administrators, security specialists, auditors, help desk, and platform deployment personnel who plan to develop, deploy, assess, or secure solutions that incorporate Microsoft 365.

Consensus Guidance

This benchmark was created using a consensus review process comprised of subject matter experts. Consensus participants provide perspective from a diverse set of backgrounds including consulting, software development, audit and compliance, security research, operations, government, and legal.

Each CIS benchmark undergoes two phases of consensus review. The first phase occurs during initial benchmark development. During this phase, subject matter experts convene to discuss, create, and test working drafts of the benchmark. This discussion occurs until consensus has been reached on benchmark recommendations. The second phase begins after the benchmark has been published. During this phase, all feedback provided by the Internet community is reviewed by the consensus team for incorporation in the benchmark. If you are interested in participating in the consensus process, please visit <https://workbench.cisecurity.org/>.

Typographical Conventions

The following typographical conventions are used throughout this guide:

Convention	Meaning
<code>Stylized Monospace font</code>	Used for blocks of code, command, and script examples. Text should be interpreted exactly as presented.
Monospace font	Used for inline code, commands, or examples. Text should be interpreted exactly as presented.
< <i>italic font in brackets</i> >	Italic texts set in angle brackets denote a variable requiring substitution for a real value.
<i>Italic font</i>	Used to denote the title of a book, article, or other publication.
Note	Additional information or caveats

Scoring Information

A scoring status indicates whether compliance with the given recommendation impacts the assessed target's benchmark score. The following scoring statuses are used in this benchmark:

Scored

Failure to comply with "Scored" recommendations will decrease the final benchmark score. Compliance with "Scored" recommendations will increase the final benchmark score.

Not Scored

Failure to comply with "Not Scored" recommendations will not decrease the final benchmark score. Compliance with "Not Scored" recommendations will not increase the final benchmark score.

Profile Definitions

The following configuration profiles are defined by this Benchmark:

- **Level 1**

Items in this profile apply to Microsoft 365 and are intend to:

- be practical and prudent;
- provide a clear security benefit; and
- not inhibit the utility of the technology beyond acceptable means.

- **Level 2**

This profile extends the "Level 1" profile. Items in this profile exhibit one or more of the following characteristics:

- are intended for environments or use cases where security is paramount
- acts as defense in depth measure
- may negatively inhibit the utility or performance of the technology.

Acknowledgements

This benchmark exemplifies the great things a community of users, vendors, and subject matter experts can accomplish through consensus collaboration. The CIS community thanks the entire consensus team with special recognition to the following individuals who contributed greatly to the creation of this guide:

Editor

Sean Sweeney
Jonathan Trull
Dan Menicucci
Gururaj Pandurangi
Shamir Charania
Karen Scarfone

Contributor

Rahul Khengare
Jordan Rakoske GSEC, GCWN

Recommendations

1 Account / Authentication

1.1 (L1) Ensure multifactor authentication is enabled for all users in administrative roles (Scored)

Profile Applicability:

- Level 1

Description:

Enable multifactor authentication for all users who are members of administrative roles in the Microsoft 365 tenant. These include roles such as:

- Global Administrator
- Billing Administrator
- Exchange Administrator
- SharePoint Administrator
- Password Administrator
- Skype for Business Administrator
- Service Administrator
- User Management Administrator
- Dynamics 365 Service Administrator
- Power BI Administrator

Rationale:

Multifactor authentication requires an individual to present a minimum of two separate forms of authentication before access is granted. Multifactor authentication provides additional assurance that the individual attempting to gain access is who they claim to be. With multifactor authentication, an attacker would need to compromise at least two different authentication mechanisms, increasing the difficulty of compromise and thus reducing the risk.

Audit:

To verify the multifactor authentication configuration for administrators, use the Microsoft 365 Admin Center:

1. Log in as a Global Administrator.

2. Go to Users > Active Users.
3. Click on More > Multifactor Authentication Setup.
4. Using the View Option, select the appropriate administrator role to review.
5. Review Users for Multifactor authentication status.

To verify the multifactor authentication configuration for administrators, use the Office 365 PowerShell MSOL:

1. Connect to Microsoft 365 using `Connect-MSOLService`.
2. Run the following PowerShell command:

```
Get-MsolRole | Where-Object {$_.Name -like "*Administrator*"} | ForEach-Object { Get-MsolRoleMember -RoleObjectId $_.ObjectId } | Select-Object EmailAddress, @{N="MFA Status"; e={$_.StrongAuthenticationRequirements.state}} -Unique
```

3. Ensure that MFA Status equals Enforced.

To verify the multifactor authentication configuration for administrators, use the M365 SecureScore service:

1. Log in to the securescore portal (<https://securescore.office.com>) using admin permissions (global admin or a custom admin role) for an Office 365 Enterprise, Microsoft 365 Business, or Office 365 Business Premium subscription.
2. Click on Require MFA for Azure AD privileged roles policy to check MFA for admin users.
3. It will show the number of Admin users who do not have MFA configured.

This information is also available via the Microsoft Graph Security API:

```
GET https://graph.microsoft.com/beta/security/secureScores
```

Remediation:

To enable multifactor authentication for administrators, use the Azure Portal:

1. Sign in to the Azure Portal as a Global Administrator, Security Administrator, or Conditional Access Administrator.
2. In the Azure Portal, on the left navbar, click Azure Active Directory.
3. On the Azure Active Directory page, in the Security section, click Conditional access.
4. In the list of policies, click the policy named Baseline policy: Require MFA for admins.
5. To enable the policy, select Use policy immediately.
6. Click Save.

To enable multifactor authentication for administrators, use the Office 365 PowerShell MSOL:

1. Connect to Microsoft 365 using `Connect-MSOLService`.
2. Run the following PowerShell command:

```
$Auth = New-Object -TypeName  
Microsoft.Online.Administration.StrongAuthenticationRequirement -Property  
@{RelyingParty = "*"; State = "Enabled"}  
  
Get-MsolRole | Where-Object {$_.Name -like "*Administrator*"} | ForEach-  
Object { Get-MsolRoleMember -RoleObjectId $_.ObjectId } | Select-Object -  
Unique | ForEach-Object { Set-MsolUser -ObjectId $_.ObjectId -  
StrongAuthenticationRequirements $Auth }
```

References:

1. <https://docs.microsoft.com/en-us/graph/api/resources/security-api-overview?view=graph-rest-beta>

CIS Controls:

Version 7

16.3 Require Multi-factor Authentication

Require multi-factor authentication for all user accounts, on all systems, whether managed onsite or by a third-party provider.

1.2 (L2) Ensure multifactor authentication is enabled for all users in all roles (Scored)

Profile Applicability:

- Level 2

Description:

Enable multifactor authentication for all users in the Microsoft 365 tenant. Users will be prompted to authenticate with a second factor upon logging in to Microsoft 365 services each day. The second factor is most commonly a text message to a registered mobile phone number where they type in an authorization code, or with a mobile application like Microsoft Authenticator.

Rationale:

Multifactor authentication requires an individual to present a minimum of two separate forms of authentication before access is granted. Multifactor authentication provides additional assurance that the individual attempting to gain access is who they claim to be. With multifactor authentication, an attacker would need to compromise at least two different authentication mechanisms, increasing the difficulty of compromise and thus reducing the risk.

Audit:

To verify the multifactor authentication configuration for all users, use the Microsoft 365 Admin Center:

1. Log in as a Global Administrator.
2. Go to Users > Active Users.
3. Click on More > Multifactor Authentication Setup.
4. Using the View Option, select Sign-in allowed users.
5. Confirm there are no users with an MFA Status set to Disabled.

To verify the multifactor authentication configuration for all users, use the Office 365 PowerShell MSOL:

1. Connect to Microsoft 365 using Connect-MSOLService.
2. Run the following PowerShell command:

```
Get-MsolUser -All | Select-Object UserPrincipalName, @{N="MFA Status";  
e={$_.StrongAuthenticationRequirements.State}}
```

3. Ensure that MFA Status equals Enforced.

Remediation:

To enable multifactor authentication for all users, use the Microsoft 365 Admin Center:

1. Log in as a Global Administrator.
2. Go to Users > Active Users.
3. Click on More > Multifactor Authentication Setup.
4. Using the View Option, select Sign-in allowed users.
5. Select all users with MFA Status set to Disabled.
6. Click Enable.

To enable multifactor authentication for all users, use the Office 365 PowerShell MSOL:

1. Connect to Microsoft 365 using Connect-MSOLService.
2. Run the following PowerShell command:

```
$Auth = New-Object -TypeName  
Microsoft.Online.Administration.StrongAuthenticationRequirement -Property  
@{RelyingParty = "*"; State = "Enabled"}  
  
Get-MsolUser -All | ForEach-Object { Set-MsolUser -UserPrincipalName  
$_ .UserPrincipalName -StrongAuthenticationRequirements $Auth }
```

Default Value:

Disabled

CIS Controls:

Version 7

16.3 Require Multi-factor Authentication

Require multi-factor authentication for all user accounts, on all systems, whether managed onsite or by a third-party provider.

1.3 (L1) Ensure that between two and four global admins are designated (Scored)

Profile Applicability:

- Level 1

Description:

More than one global administrator should be designated so a single admin can be monitored and to provide redundancy should a single admin leave an organization. Additionally, there should be no more than four global admins set for any tenant.

Rationale:

If there is only one global tenant administrator, he or she can perform malicious activity without the possibility of being discovered by another admin. If there are numerous global tenant administrators, the more likely it is that one of their accounts will be successfully breached by an external attacker.

Audit:

To verify the number of global tenant administrators, use the Microsoft 365 Admin Center:

1. Select `Users > Active Users`.
2. Set `Views` to `Global Admins`.
3. Review the list of `Global Admins` to confirm there are from two to four such accounts.

To verify the number of global tenant administrators, you can also use the Office 365 PowerShell MSOL:

1. Connect to Microsoft 365 using `Connect-MSOLService`
2. Run the following PowerShell commands:

```
$role = Get-MsolRole -RoleName "Company Administrator"  
Get-MsolRoleMember -RoleObjectId $role.objectid
```

Remediation:

To correct the number of global tenant administrators, use the Microsoft 365 Admin Center:

1. Select Users > Active Users.
2. Set Views to Global Admins.
3. To create a new Global Admin:
 1. Select Add Users.
 2. Enter User Information.
 3. Select Roles.
 4. Select Global Administrator.
 5. Click Add.
4. To remove Global Admins:
 1. Select User.
 2. Select Edit under Roles.
 3. Select Customized administrator and chose appropriate role.
 4. Click Save.

CIS Controls:

Version 7

4.1 Maintain Inventory of Administrative Accounts

Use automated tools to inventory all administrative accounts, including domain and local accounts, to ensure that only authorized individuals have elevated privileges.

1.4 (L1) Ensure self-service password reset is enabled (Scored)

Profile Applicability:

- Level 1

Description:

Enabling self-service password reset allows users to reset their own passwords in Azure AD. When your users sign in to Microsoft 365, they will be prompted to enter additional contact information that will help them reset their password in the future.

Self-service password reset is free for cloud users with Microsoft 365 business, non-profit or education plans. It doesn't work with trial subscriptions. If you are using On-premise AD and syncing your users, it requires a paid subscription to Azure AD Premium.

Rationale:

Users will no longer need to engage the helpdesk for password resets, and the password reset mechanism will automatically block common, easily guessable passwords.

Audit:

To verify self-service password reset is enabled, use the Microsoft 365 Admin Center:

1. Choose `Settings > Security & privacy`.
2. Choose the link to `go to the Azure admin center`.
3. Choose `Users and groups > Password reset`.
4. On the Properties page, check the selected option.

Remediation:

To enable self-service password reset, use the Microsoft 365 Admin Center:

1. Choose `Settings > Security & privacy`.
2. Choose the link to `go to the Azure admin center`.
3. Choose `Users and groups > Password reset`.
4. On the Properties page, choose `All` to enable it for everyone in your business, and then choose `Save`.

References:

1. <https://support.office.com/en-us/article/let-users-reset-their-own-passwords-in-office-365-5bc3f460-13cc-48c0-abd6-b80bae72d04a>
2. <https://gallery.technet.microsoft.com/office/Enable-Self-Service-59846d88>

3. <https://docs.microsoft.com/en-us/azure/active-directory/authentication/quickstart-sspr>

1.5 (L1) Ensure modern authentication for Exchange Online is enabled (Scored)

Profile Applicability:

- Level 1

Description:

Modern authentication in Microsoft 365 enables authentication features like multifactor authentication (MFA) using smart cards, certificate-based authentication (CBA), and third-party SAML identity providers. When you enable modern authentication in Exchange Online, Outlook 2016 and Outlook 2013 use modern authentication to log in to Microsoft 365 mailboxes. When you disable modern authentication in Exchange Online, Outlook 2016 and Outlook 2013 use basic authentication to log in to Microsoft 365 mailboxes.

When users initially configure certain email clients, like Outlook 2013 and Outlook 2016, they may be required to authenticate using enhanced authentication mechanisms, such as multifactor authentication. Other Outlook clients that are available in Microsoft 365 (for example, Outlook Mobile and Outlook for Mac 2016) always use modern authentication to log in to Microsoft 365 mailboxes.

Rationale:

Strong authentication controls, such as the use of multifactor authentication, may be circumvented if basic authentication is used by Exchange Online email clients such as Outlook 2016 and Outlook 2013. Enabling modern authentication for Exchange Online ensures strong authentication mechanisms are used when establishing sessions between email clients and Exchange Online.

Audit:

To verify modern authentication is enabled, use the Exchange Online PowerShell Module:

1. Run the Microsoft Exchange Online PowerShell Module.
2. Connect to Exchange Online using `Connect-EXOPSSession`.
3. Run the following PowerShell command:

```
Get-OrganizationConfig | Format-Table -Auto Name, OAuth*
```

4. Verify `OAuth2ClientProfileEnabled` is `True`.

Remediation:

To enable modern authentication, use the Exchange Online PowerShell Module:

1. Run the Microsoft Exchange Online PowerShell Module.
2. Connect to Exchange Online using `Connect-EXOPSSession`.
3. Run the following PowerShell command:

```
Set-OrganizationConfig -OAuth2ClientProfileEnabled $True
```

Default Value:

True

References:

1. <https://support.office.com/en-gb/article/enable-or-disable-modern-authentication-in-exchange-online-58018196-f918-49cd-8238-56f57f38d662>

CIS Controls:

Version 7

16.3 Require Multi-factor Authentication

Require multi-factor authentication for all user accounts, on all systems, whether managed onsite or by a third-party provider.

16.5 Encrypt Transmittal of Username and Authentication Credentials

Ensure that all account usernames and authentication credentials are transmitted across networks using encrypted channels.

1.6 (L1) Ensure modern authentication for SharePoint applications is required (Scored)

Profile Applicability:

- Level 1

Description:

Modern authentication in Microsoft 365 enables authentication features like multifactor authentication (MFA) using smart cards, certificate-based authentication (CBA), and third-party SAML identity providers

Rationale:

Strong authentication controls, such as the use of multifactor authentication, may be circumvented if basic authentication is used by SharePoint applications. Requiring modern authentication for SharePoint applications ensures strong authentication mechanisms are used when establishing sessions between these applications, SharePoint, and connecting users.

Audit:

To verify SharePoint settings, use the Microsoft 365 Admin Center:

1. Select `SharePoint`.
2. Select `Access Control`.
3. Verify that `Apps that don't use modern authentication is set to Block`.

To verify Apps that don't use modern authentication is set to Block, use the SharePoint Online PowerShell Module:

1. Connect to SharePoint Online using `Connect-SPOService`.
2. Run the following Sharepoint Online PowerShell command:

```
Get-SPTenant | ft LegacyAuthProtocolsEnabled
```

3. Verify `LegacyAuthProtocolsEnabled` is set `False`

Remediation:

To set SharePoint settings, use the Microsoft 365 Admin Center:

1. Select SharePoint.
2. Select Access Control.
3. Set Apps that don't use modern authentication to Block.
4. Click OK.

To set Apps that don't use modern authentication is set to Block, use the SharePoint Online PowerShell Module:

1. Connect to SharePoint Online using `Connect-SPOService`.
2. Run the following Sharepoint Online PowerShell command:

```
Set-SPTenant -LegacyAuthProtocolsEnabled $false
```

CIS Controls:

Version 7

4.5 Use Multifactor Authentication For All Administrative Access

Use multi-factor authentication and encrypted channels for all administrative account access.

1.7 (L1) Ensure modern authentication for Skype for Business Online is enabled (Scored)

Profile Applicability:

- Level 1

Description:

Modern authentication in Microsoft 365 enables authentication features like multifactor authentication (MFA) using smart cards, certificate-based authentication (CBA), and third-party SAML identity providers. When you enable modern authentication in Skype for Business, the Skype for Business client uses modern authentication to log in to Skype for Business Online.

Rationale:

Strong authentication controls, such as the use of multifactor authentication, may be circumvented if basic authentication is used by Skype for Business Online clients. Enabling modern authentication for Skype for Business Online ensures strong authentication mechanisms are used when establishing sessions between clients and Skype for Business Online.

Audit:

To verify modern authentication is enabled, use the Skype for Business Online PowerShell Module:

1. Connect to Skype for Business Online using the following Powershell commands:

```
Import-Module SkypeOnlineConnector  
$sfbSession = New-CsOnlineSession  
Import-PSSession $sfbSession
```

2. Run the following PowerShell command to verify that modern authentication is enabled:

```
Get-CsOauthConfiguration |fl ClientAdalAuthOverride
```

3. Verify that `ClientAdalAuthOverride` is set to `Allowed`.

Remediation:

To enable modern authentication, use the Skype for Business Online PowerShell Module:

1. Connect to Skype for Business Online using the following Powershell commands:

```
Import-Module SkypeOnlineConnector  
$sfbSession = New-CsOnlineSession  
Import-PSSession $sfbSession
```

2. Run the following PowerShell command to verify that modern authentication is enabled:

```
Set-CsOauthConfiguration -ClientAdalAuthOverride Allowed
```

References:

1. <https://social.technet.microsoft.com/wiki/contents/articles/34339.skype-for-business-online-enable-your-tenant-for-modern-authentication.aspx>

CIS Controls:

Version 7

4.5 Use Multifactor Authentication For All Administrative Access

Use multi-factor authentication and encrypted channels for all administrative account access.

1.8 (L1) Ensure that Office 365 Passwords Are Not Set to Expire (Scored)

Profile Applicability:

- Level 1

Description:

Review the password expiration policy, to ensure that user passwords in Office 365 are not set to expire.

Rationale:

NIST has updated their recommendation to not arbitrarily require users to change their passwords after a specific amount of time, unless there is evidence that the password is compromised or the user forgot it.

Audit:

To verify Office 365 Passwords Are Not Set to Expire, use the Microsoft 365 Admin Center:

1. Go to Settings > Security & Privacy.
2. Click `Edit` next to Password Policy.
3. Ensure that `Set user passwords to never expire` is set to `On`.

To verify Office 365 Passwords Are Not Set to Expire, use the Microsoft Online PowerShell Module:

1. Connect to Microsoft Online service using `Connect-MSOLService`.
2. Run the following Microsoft Online PowerShell command:

```
Get-MsolPasswordPolicy -DomainName <DomainName> | ft ValidityPeriod
```

Remediation:

To set Office 365 Passwords to Expire, use the Microsoft 365 Admin Center:

1. Go to Settings>Security & Privacy.
2. Click `Edit` next to Password Policy.
3. Ensure that `Set user passwords to never expire` is set to `On`.

To set Office 365 Passwords Are Not Set to Expire, use the Microsoft Online PowerShell Module:

1. Connect to Microsoft Online service using `Connect-MSOLService`.
2. Run the following Microsoft Online PowerShell command:

```
Set-MsolPasswordPolicy -ValidityPeriod 2147483647 -DomainName <DomainName> -  
NotificationDays 30
```

2 Application Permissions

2.1 (L2) Ensure third party integrated applications are not allowed (Scored)

Profile Applicability:

- Level 2

Description:

Do not allow third party integrated applications to connect to your services.

Rationale:

You should not allow third party integrated applications to connect to your services unless there is a very clear value and you have robust security controls in place. While there are legitimate uses, attackers can grant access from breached accounts to third party applications to exfiltrate data from your tenancy without having to maintain the breached account.

Audit:

To verify that third party integrated applications are not allowed, use the Microsoft 365 Admin Center:

1. Click `Security and Compliance`.
2. Select `Admin Centers` and `Azure Active Directory`.
3. Select `Users Settings`.
4. Verify `App Registrations` is set to `No`.

Remediation:

To prohibit third party integrated applications, use the Microsoft 365 Admin Center:

1. Click `Security and Compliance`.
2. Select `Admin Centers` and `Azure Active Directory`.
3. Select `Users Settings`.
4. Set `App Registrations` to `No`.

Default Value:

Yes

CIS Controls:

Version 7

18.4 Only Use Up-to-date And Trusted Third-Party Components

Only use up-to-date and trusted third-party components for the software developed by the organization.

2.2 (L2) Ensure calendar details sharing with external users is disabled (Scored)

Profile Applicability:

- Level 2

Description:

You should not allow your users to share the full details of their calendars with external users.

Rationale:

Attackers often spend time learning about your organization before launching an attack. Publicly available calendars can help attackers understand organizational relationships and determine when specific users may be more vulnerable to an attack, such as when they are traveling.

Audit:

To verify calendar details sharing with external users is disabled, use the Microsoft 365 Admin Center:

1. Select `Admin Center` and Click `Settings`.
2. Click `Services` and `add-ins`.
3. Click `Calendar`.
4. Verify `Let your users share their calendars with external users who have O365 or Exchange` is set to `Off`.

To verify calendar details sharing with external users is disabled, use the Exchange Online PowerShell Module:

1. Connect to Exchange Online using `Connect-EXOPSSession`.
2. Run the following Exchange Online PowerShell command:

```
Get-SharingPolicy | Where-Object { $_.Domains -like '*CalendarSharing*' }
```

3. Verify `Enabled` is set to `False`

Remediation:

To disable calendar details sharing with external users, use the Microsoft 365 Admin Center:

1. Select `Admin Center` and Click `Settings`.
2. Click `Services` and add-ins.
3. Click `Calendar`.
4. Set `Let your users share their calendars with external users who have O365 or Exchange` to `Off`.
5. Click `Save`.

To disabled calendar details sharing with external users policy, use the Exchange Online PowerShell Module:

1. Connect to Exchange Online using `Connect-EXOPSSession`.
2. Run the following Exchange Online PowerShell command:

```
Set-SharingPolicy -Identity "Name of the policy" -Enabled $False
```

Default Value:

On

2.3 (L2) Ensure O365 ATP SafeLinks for Office Applications is Enabled (Scored)

Profile Applicability:

- Level 2

Description:

Enabling the Advanced Threat Protection (ATP) Safe Links policy for Office applications allows URL's that existing inside of Office documents opened by Office, Office Online and Office mobile to be processed against ATP time-of-click verification.

Rationale:

ATP Safe Links for Office applications extends phishing protection to documents that contain hyperlinks, even after they have been delivered to a user.

Audit:

To verify the ATP Safe Links policy for Office is enabled, use the Microsoft 365 Admin Center:

1. Click `Security & Compliance` to open the Security & Compliance portal.
2. Navigate to `Threat management > Policy > ATP Safe Links`.
3. Under Policies that apply to the entire organization specific recipients, verify that at least one policy exists and click `Edit`.
4. Under Settings that apply to content except email:
 1. Verify that `Office 365 ProPlus`, `Office for iOS and Android` is checked.
 2. Verify that `Office Online` of above applications is checked`.
 3. Verify that `Do not let users click through safe links to original URL` is checked.

To verify the ATP Safe Links policy is enabled, use the Exchange Online PowerShell Module:

1. Connect using `Connect-EXOPSSession`.
2. Run the following PowerShell command:

```
Get-AtpPolicyForO365 | fl  
Name,AllowClickThrough,EnableSafeLinksForClients,EnableSafeLinksForWebAccessC  
ompanion,EnableSafeLinksForO365Clients
```

3. Verify the value for `AllowClickThrough` is set to `False` and the rest are set for `True`.

Remediation:

To enable the ATP Safe Links policy for Office, use the Microsoft 365 Admin Center:

1. Click `Security & Compliance` to open the Security & Compliance portal.
2. Navigate to `Threat management > Policy > ATP Safe Links`.
3. Under Policies that apply to the entire organization specific recipients, verify that at least one policy exists and click `Edit`.
 1. Ensure that `Office 365 ProPlus`, `Office for iOS and Android` is checked.
 2. Ensure that `Office Online` of above applications is checked.
 3. Ensure that `Do not let users click through safe links to original URL` is checked.

To enable the ATP Safe Links policy for Office 365, use the Exchange Online PowerShell Module:

1. Connect using `Connect-EXOPSSession`.
2. Run the following PowerShell command:

```
Set-AtpPolicyForO365 -AllowClickThrough $False -EnableSafeLinksForClients $true -EnableSafeLinksForWebAccessCompanion $True
```

CIS Controls:

Version 7

7.4 Maintain and Enforce Network-Based URL Filters

Enforce network-based URL filters that limit a system's ability to connect to websites not approved by the organization. This filtering shall be enforced for each of the organization's systems, whether they are physically at an organization's facilities or not.

2.4 (L2) Ensure Office 365 ATP for SharePoint, OneDrive, and Microsoft Teams is Enabled (Scored)

Profile Applicability:

- Level 2

Description:

Office 365 ATP for SharePoint, OneDrive, and Microsoft Teams scans these services for malicious files.

Rationale:

Office 365 ATP for SharePoint, OneDrive, and Microsoft Teams protects your organization from inadvertently sharing malicious files. When a malicious file is detected, that file is blocked so that no one can open, copy, move, or share it until further actions are taken by the organization's security team.

Audit:

To verify that Office 365 ATP is enabled for SharePoint, OneDrive, and Microsoft Teams, use the Microsoft 365 Admin Center:

1. Click `Security & Compliance` to open the Security & Compliance portal.
2. Verify that `Turn on ATP for SharePoint, OneDrive, and Microsoft Teams` is checked.

To verify that Office 365 ATP is enabled for SharePoint, OneDrive, and Microsoft Teams, use the Exchange Online PowerShell Module:

1. Connect using `Connect-EXOPSSession`.
2. Run the following PowerShell command:

```
Get-AtpPolicyForO365 | fl Name,EnableATPForSPOTeamsODB
```

3. Verify the value for `EnableATPForSPOTeamsODB` is set to `True`.

Remediation:

To enable Office 365 ATP for SharePoint, OneDrive, and Microsoft Teams, use the Microsoft 365 Admin Center:

1. Click `Security & Compliance` to open the Security & Compliance portal.

2. Ensure that Turn on ATP for SharePoint, OneDrive, and Microsoft Teams is checked.

To enable O365 ATP for SharePoint, OneDrive, and Microsoft Teams, use the Exchange Online PowerShell Module:

1. Connect using Connect-EXOPSSession.
2. Run the following PowerShell command:

```
Set-AtpPolicyForO365 -EnableATPForSPOTeamsODB $True
```

CIS Controls:

Version 7

7.4 Maintain and Enforce Network-Based URL Filters

Enforce network-based URL filters that limit a system's ability to connect to websites not approved by the organization. This filtering shall be enforced for each of the organization's systems, whether they are physically at an organization's facilities or not.

3 Data Management

3.1 (L2) Ensure the customer lockbox feature is enabled (Scored)

Profile Applicability:

- Level 2

Description:

You should enable the Customer Lockbox feature. It requires Microsoft to get your approval for any datacenter operation that grants a Microsoft support engineer or other employee direct access to any of your data. For example, in some cases a Microsoft support engineer might need access to your Microsoft 365 content in order to help troubleshoot and fix an issue for you. Customer lockbox requests also have an expiration time, and content access is removed after the support engineer has fixed the issue.

Rationale:

Enabling this feature protects your data against data spillage and exfiltration.

Audit:

To verify the Customer Lockbox feature is enabled, use the Microsoft 365 Admin Portal:

1. Browse to <https://portal.office.com/AdminPortal/Home?switchtomoderndefault=true#/settings/security>.
2. Click `Edit` next to `Customer Lockbox`.
3. Check that the value of `Require approval for all data access requests` is set to `On`.

To verify the Customer Lockbox feature is enabled, use the Microsoft 365 SecureScore Portal:

1. Log in to the Microsoft 365 SecureScore portal (<https://seurescore.microsoft.com>) using admin permissions (global admin or a custom admin role) for an Office 365 Enterprise, Microsoft 365 Business, or Office 365 Business Premium subscription.
2. Click on `Turn on customer lockbox feature` policy to check the Customer Lockbox feature.

To verify the Customer Lockbox feature is enabled, use the REST API:

```
GET https://graph.microsoft.com/beta/security/secureScores
```

Remediation:

To enable the Customer Lockbox feature, use the Microsoft 365 Admin Portal:

1. Browse to <https://portal.office.com/AdminPortal/Home?switchtomoderndefault=true#/settings/security>.
2. Click **Edit** next to **Customer Lockbox**.
3. Click the box next to **Require approval for all data access requests** to enable the feature and then click **Save**.

Default Value:

Disabled

CIS Controls:

Version 7

13 Data Protection

Data Protection

13.4 Only Allow Access to Authorized Cloud Storage or Email Providers

Only allow access to authorized cloud storage or email providers.

3.2 (L2) Ensure SharePoint Online data classification policies are set up and used (Not Scored)

Profile Applicability:

- Level 2

Description:

You should set up and use SharePoint Online data classification policies on data stored in your SharePoint Online sites.

Rationale:

The policies will help categorize your most important data so you can effectively protect it from illicit access, and will help make it easier to investigate discovered breaches.

Audit:

To verify data classification policies are set up, use the Microsoft 365 Admin Center:

1. Select `Security and Compliance`.
2. Select `Data Governance` and then `Retention`.
3. Click 'Labels'.
4. Ensure Labels exist.

Remediation:

To set up data classification policies, use the Microsoft 365 Admin Center:

1. Select `Security and Compliance`.
2. Select `Data Governance` and then `Retention`.
3. Select 'Labels'.
4. Click `Create` to create a label.

References:

1. <https://msdn.microsoft.com/en-us/library/mt718319.aspx>

CIS Controls:

Version 7

13 Data Protection

Data Protection

3.3 (L2) Ensure external domains are not allowed in Skype or Teams (Not Scored)

Profile Applicability:

- Level 2

Description:

Disable the ability of your users to communicate via Skype or Teams with users outside your organization.

Rationale:

You should not allow your users to communicate with Skype users outside your organization. While there are legitimate, productivity-improving scenarios for this, it also represents a potential security threat because those external users will be able to interact with your users over Skype for Business. Attackers may be able to pretend to be someone your user knows and then send malicious links or attachments, resulting in an account breach or leaked information.

Audit:

To verify Skype access with external users is disabled, use the Microsoft 365 Admin Center:

1. Select `Admin Centers` and `Teams and Skype`.
2. Select `Org Wide Settings` and `External Access`.
3. Verify `External Access` and `Users can communicate with external Skype users` are set to `Off`.

Remediation:

To disable Skype access with external users, use the Microsoft 365 Admin Center:

1. Select `Admin Centers` and `Teams and Skype`.
2. Select `Org Wide Settings` and `External Access`.
3. Set `External Access` and `Users can communicate with external Skype users` to `Off`.

Default Value:

On

CIS Controls:

Version 7

12.4 Deny Communication over Unauthorized Ports

Deny communication over unauthorized TCP or UDP ports or application traffic to ensure that only authorized protocols are allowed to cross the network boundary in or out of the network at each of the organization's network boundaries.

3.4 (L1) Ensure DLP policies are enabled (Scored)

Profile Applicability:

- Level 1

Description:

Enabling Data Loss Prevention (DLP) policies allows Exchange Online and SharePoint Online content to be scanned for specific types of data like social security numbers, credit card numbers, or passwords.

Rationale:

Enabling DLP policies alerts users and administrators that specific types of data should not be exposed, helping to protect the data from accidental exposure.

Audit:

To verify DLP policies are enabled, use the Microsoft 365 Admin Center:

1. Select `Security and Compliance`.
2. Select `Data loss prevention`.
3. Click `Policy`.
4. Click `Create a policy`.

To verify the DLP feature is enabled, use the Microsoft 365 SecureScore Portal:

1. Login to Microsoft 365 SecureScore portal (<https://securescore.microsoft.com>) using admin permissions (global admin or a custom admin role) for an Office 365 Enterprise, Microsoft 365 Business, or Office 365 Business Premium subscription.
2. Click on `Apply Data Loss Prevention policies` policy to check customer lockbox feature.
3. Check the number of data loss prevention policy applied

To verify the DLP feature is enabled, use the REST API:

```
GET https://graph.microsoft.com/beta/security/secureScores
```

Remediation:

To enable DLP policies, use the Microsoft 365 Admin Center:

1. Select Security and Compliance.
2. Select Data loss prevention.
3. Click Policy.
4. Click Create a policy.

CIS Controls:

Version 7

13 Data Protection

Data Protection

3.5 (L2) Ensure that external users cannot share files, folders, and sites they do not own (Scored)

Profile Applicability:

- Level 2

Description:

SharePoint gives users the ability to share files, folder, and site collections. Internal users can share with external collaborators, who with the right permissions, could share those to another external party.

Rationale:

Sharing and collaboration are key; however, file, folder, or site collection owners should have the authority over what external users get shared with to prevent unauthorized disclosures of information.

Audit:

To verify SharePoint sharing settings, use the Microsoft 365 Admin Center:

1. Select `SharePoint`.
2. Select `Sharing`.
3. Verify that `Prevent external users from sharing files, folders, and sites that they don't own` is set to `Enabled`.

To verify Prevent external users from sharing files, folders, and sites that they don't own, use the SharePoint Online PowerShell Module:

1. Connect to SharePoint Online service using `Connect-SPOService`.
2. Run the following SharePoint Online PowerShell command:

```
Get-SPOtenant | ft PreventExternalUsersFromResharing
```

3. Verify `PreventExternalUsersFromResharing` is set `True`

Remediation:

To set SharePoint sharing settings, use the Microsoft 365 Admin Center:

1. Select `SharePoint`.
2. Select `Sharing`.
3. Set `Prevent external users from sharing files, folders, and sites that they don't own` to `Enabled`.
4. Click `OK`.

To Set Prevent external users from sharing files, folders, and sites that they don't own, use the SharePoint Online PowerShell Module:

1. Connect to SharePoint Online service using `Connect-MSOLService`.
2. Run the following SharePoint Online PowerShell command:

```
Set-SPOTenant -PreventExternalUsersFromResharing $True
```

CIS Controls:

Version 7

13 Data Protection

Data Protection

3.6 (L2) Ensure external file sharing in Teams is enabled for only approved cloud storage services (Not Scored)

Profile Applicability:

- Level 2

Description:

Microsoft Teams enables collaboration via file sharing. This file sharing is conducted within Teams, using SharePoint Online, by default; however, third-party cloud services are allowed as well.

Rationale:

Ensuring that only authorized cloud storage providers are accessible from Teams will help to dissuade the use of non-approved storage providers.

Audit:

To verify external file sharing in Teams, use the Microsoft 365 Admin Center:

1. Select `Teams` and `Skype`.
2. Select `Org-wide settings`.
3. Click `Team Settings`.
4. Verify `Files` is set to `On` for only authorized cloud storage options.

Remediation:

To Set external file sharing in Teams, use the Microsoft 365 Admin Center:

1. Select `Teams` and `Skype`.
2. Select `Org-wide settings`.
3. Click `Team Settings`.
4. Set each cloud storage service under `Files` to `On` if it is authorized.

Default Value:

`On`

CIS Controls:

Version 7

13 Data Protection

Data Protection

4 Email Security / Exchange Online

4.1 (L1) Ensure the Common Attachment Types Filter is enabled (Scored)

Profile Applicability:

- Level 1

Description:

The Common Attachment Types Filter lets a user block known and custom malicious file types from being attached to emails.

Rationale:

Blocking known malicious file types can help prevent malware-infested files from infecting a host.

Audit:

To verify the Common Attachment Types Filter is enabled, use the Microsoft 365 Admin Portal:

1. Navigate to the Exchange Admin Center and click `Protection > Malware Filter`.
2. Edit the `Default` profile.
3. In the Edit tab under `Settings`, verify that the `Common Attachment Types Filter` has the value of 'On - Emails with attachments of filtered file types will trigger the Malware Detection Response (recommended).'

To verify the Common Attachment Types Filter is enabled, use the Exchange Online PowerShell Module:

1. Connect to Exchange Online using `Connect-EXOPSSession`.
2. Run the following Exchange Online PowerShell command:

```
Get-MalwareFilterPolicy -Identity Default | Select-Object EnableFileFilter
```

3. Verify `EnableFileFilter` is set to `True`.

Remediation:

To enable the Common Attachment Types Filter, use the Microsoft 365 Admin Portal:

1. Navigate to the Exchange Admin Center and click `Protection > Malware Filter`.

2. Edit the `Default` profile.
3. Click on the `Edit` tab under `Settings`. Ensure that the `Common Attachment Types Filter` has the value of `On - Emails with attachments of filtered file types will trigger the Malware Detection Response (recommended)`.

To enable the Common Attachment Types Filter, use the Exchange Online PowerShell Module:

1. Connect to Exchange Online using `Connect-EXOPSSession`.
2. Run the following Exchange Online PowerShell command:

```
Set-MalwareFilterPolicy -Identity Default -EnableFileFilter $true
```

Default Value:

off

References:

1. <https://docs.microsoft.com/en-us/powershell/module/exchange/antispam-antimalware/Get-MalwareFilterPolicy?view=exchange-ps>
2. <https://docs.microsoft.com/en-us/office365/SecurityCompliance/configure-anti-malware-policies#use-remote-powershell-to-configure-anti-malware-policies>

CIS Controls:

Version 7

8.1 Utilize Centrally Managed Anti-malware Software

Utilize centrally managed anti-malware software to continuously monitor and defend each of the organization's workstations and servers.

4.2 (L1) Ensure Exchange Online Spam Policies are set correctly (Scored)

Profile Applicability:

- Level 1

Description:

You should set your Exchange Online Spam Policies to copy emails and notify someone when a sender in your tenant has been blocked for sending spam emails.

Rationale:

A blocked account is a good indication that the account in question has been breached and an attacker is using it to send spam emails to other people.

Audit:

To verify the Exchange Online Spam Policies are set correctly, use the Microsoft 365 Admin Center:

1. Select `Exchange`.
2. Navigate to `Protection > Outbound Spam`.
3. Edit the `Default` profile.
4. Select `Outbound spam preferences`.
5. Verify both `Send a copy of all suspicious outbound email messages to the following email address or addresses` and `Send a notification to the following email address or addresses when a sender is blocked for sending outbound spam` are checked and the email addresses to be notified are correct.

To verify the Exchange Online Spam Policies are set correctly, use the Exchange Online PowerShell Module:

1. Connect to Exchange Online using `Connect-EXOPSSession`.
2. Run the following PowerShell command:

```
Get-HostedOutboundSpamFilterPolicy | Select-Object Bcc*, Notify*
```

3. Verify both `BccSuspiciousOutboundMail` and `NotifyOutboundSpam` are set to `True` and the email addresses to be notified are correct.

Remediation:

To set the Exchange Online Spam Policies correctly, use the Microsoft 365 Admin Center:

1. Select `Exchange`.
2. Navigate to `Protection > Outbound Spam`.
3. Edit the `Default` profile.
4. Select `Outbound spam preferences`.
5. Check `Send a copy of all suspicious outbound email messages to the following email address or addresses` and enter the email address(es).
6. Check `Send a notification to the following email address or addresses when a sender is blocked for sending outbound spam` and enter the email address(es).
7. Click `Save`.

To set the Exchange Online Spam Policies correctly, use the Exchange Online PowerShell Module:

1. Connect to Exchange Online using `Connect-EXOPSSession`.
2. Run the following PowerShell command:

```
$BccEmailAddress = @"<INSERT-EMAIL>"  
  
$NotifyEmailAddress = @"<INSERT-EMAIL>"  
  
Set-HostedOutboundSpamFilterPolicy -Identity Default -  
BccSuspiciousOutboundAdditionalRecipients $BccEmailAddress -  
BccSuspiciousOutboundMail $true -NotifyOutboundSpam $true -  
NotifyOutboundSpamRecipients $NotifyEmailAddress
```

Default Value:

disabled

CIS Controls:

Version 7

7 Email and Web Browser Protections

Email and Web Browser Protections

4.3 (L1) Ensure mail transport rules do not forward email to external domains (Scored)

Profile Applicability:

- Level 1

Description:

You should set your Exchange Online mail transport rules to not forward email to domains not registered in your tenancy.

Rationale:

Attackers often create these rules to exfiltrate data from your tenancy.

Audit:

To verify the mail transport rules do not forward email to external domains, use the Microsoft 365 Admin Center:

1. Select `Exchange`.
2. Select `Mail Flow and Rules`.
3. Review the rules and verify that none of them are forwards to external domains.

To verify that no rules are forwarding email to external domains, you can also use the Exchange Online PowerShell module:

1. Connect to Exchange online using `Connect-EXOPSSession`
2. Run the following PowerShell command to review the Transport Rules that are redirecting email:

```
Get-TransportRule | Where-Object {$_.RedirectMessageTo -ne $null} | ft  
Name,RedirectMessageTo
```

3. Verify that none of the addresses are going to external domains

Remediation:

To alter the mail transport rules so they do not forward email to external domains, use the Microsoft 365 Admin Center:

1. Select `Exchange`.
2. Select `Mail Flow and Rules`.

3. For each rule that forwards email to external domains, select the rule and click the 'Delete' icon.

CIS Controls:

Version 7

7 Email and Web Browser Protections

Email and Web Browser Protections

4.4 (L1) Ensure mail transport rules do not whitelist specific domains (Scored)

Profile Applicability:

- Level 1

Description:

You should set your Exchange Online mail transport rules so they do not whitelist any specific domains.

Rationale:

Whitelisting domains in transport rules bypasses regular malware and phishing scanning, which can enable an attacker to launch attacks against your users from a safe haven domain.

Audit:

To verify the mail transport rules do not whitelist any specific domains, use the Microsoft 365 Admin Center:

1. Select `Exchange`.
2. Select `Mail Flow and Rules`.
3. Review the rules and verify that none of them whitelist any specific domains.

To verify that mail transport rules do not whitelist any domains, you can also use the Exchange Online PowerShell:

1. Connect to Exchange online using `Connect-EXOPSSession`
2. Run the following PowerShell command:

```
Get-TransportRule | Where-Object {($_.setscl -eq -1 -and $_.SenderDomainIs -ne $null)} | ft Name,SenderDomainIs
```

Remediation:

To alter the mail transport rules so they do not whitelist any specific domains, use the Microsoft 365 Admin Center:

1. Select `Exchange`.
2. Select `Mail Flow and Rules`.

3. For each rule that whitelists specific domains, select the rule and click the 'Delete' icon.

CIS Controls:

Version 7

7 Email and Web Browser Protections

Email and Web Browser Protections

4.5 (L2) Ensure the Client Rules Forwarding Block is enabled (Scored)

Profile Applicability:

- Level 2

Description:

You should enable the Client Rules Forwarding Block, which prevents the use of any client-side rules that forward email to an external domain.

Rationale:

The use of client-side forwarding rules to exfiltrate data to external recipients is an increasingly used vector for data exfiltration by bad actors.

Audit:

To verify the Client Rules Forwarding Block is enabled, use the Microsoft 365 Admin Center:

1. Go to Exchange Admin Center.
2. Select mail flow.
3. Select Rules.
4. Verify that 'Client Rules To External Block' exists.

To verify the Client Rules Forwarding Block is enabled, use the Exchange Online PowerShell Module:

1. Connect to Exchange Online using `Connect-EXOPSSession`.
2. Run the following Exchange Online PowerShell command:

```
Get-TransportRule | where { $_.Identity -like '*Client Rules To External Block*' }
```

3. Verify that 'Client Rules To External Block' state is set to Enabled.

Remediation:

To enable the Client Rules Forwarding Block, use the Microsoft 365 Admin Center

1. Go to Security and Compliance.
2. Go to Secure Score.
3. Select Client Rules Forwarding Block.
4. Select Learn More.

5. Select `Apply`.

To create the Client Rules Forwarding Block, use the Exchange Online PowerShell Module:

1. Connect to Exchange Online using `Connect-EXOPSSession`.
2. Run the following Exchange Online PowerShell commands to create a rule:

```
$rejectMessageText = "To improve security, auto-forwarding rules to external addresses has been disabled. Please contact your Microsoft Partner if you'd like to set up an exception."
```

```
New-TransportRule -name "Client Rules To External Block" -Priority 1 -SentToScope NotInOrganization -FromScope InOrganization -MessageTypeMatches AutoForward -RejectMessageEnhancedStatusCode 5.7.1 -RejectMessageReasonText $rejectMessageText
```

3. Verify that `Client Rules To External Block` gets created.

CIS Controls:

Version 7

7 Email and Web Browser Protections

Email and Web Browser Protections

4.6 (L2) Ensure the Advanced Threat Protection Safe Links policy is enabled (Scored)

Profile Applicability:

- Level 2

Description:

Enabling the Advanced Threat Protection (ATP) Safe Links policy allows email messages that include URLs to be processed and rewritten if required. ATP Safe Links provides time-of-click verification of web addresses in email messages and Office documents.

Rationale:

ATP Safe Links extends phishing protection to include redirecting all email hyperlinks through a forwarding service which will block malicious ones even after the email has been delivered to the end user.

Audit:

To verify the ATP Safe Links policy is enabled, use the Microsoft 365 Admin Center:

1. Click `Security & Compliance` to open the Security & Compliance portal.
2. Navigate to `Threat management > Policy > ATP Safe Links`.
3. Under `Policies` that apply to specific recipients, verify that at least one policy exists and click `Edit`.
4. Select `Settings`.
5. Verify `Select the action for unknown potentially malicious URLs in messages` is set to `On`.
6. Verify that at least both `Use safe attachments to scan downloadable content`, `Do not let users click through safe links to original URL` and `Apply safe links to messages sent within the organization` are checked.

To verify the ATP Safe Links policy is enabled, use the Exchange Online PowerShell Module:

1. Connect using `Connect-EXOPSSession`.
2. Run the following PowerShell command:

```
Get-SafeLinksPolicy | Select-Object Name, IsEnabled, ScanUrls, EnableForInternalSenders, AllowClickThrough
```

3. Verify the values for `IsEnabled` and `ScanUrls` are set to `True`, and `AllowClickThrough` is set to `False`.

Remediation:

To enable the ATP Safe Links policy, use the Microsoft 365 Admin Center:

1. Click `Security & Compliance` to open the Security & Compliance portal.
2. Navigate to `Threat management > Policy > ATP Safe Links`.
3. Under `Policies` that apply to specific recipients, verify that at least one policy exists and click `Edit`, or create a new policy.
4. Select `Settings`.
5. Select `On` for `Select the action for unknown potentially malicious URLs in messages`.
6. Check `Use safe attachments to scan downloadable content`.
7. Check `Apply safe links to messages sent within the organization`.
8. Check `Do not let users click through safe links to original URL`.
9. Click `Save`.

To enable the ATP Safe Links policy, use the Exchange Online PowerShell Module:

1. Connect using `Connect-EXOPSSession`.
2. Run the following PowerShell command:

```
$SafeLinksPolicy = Get-SafeLinksPolicy

If (-not $SafeLinksPolicy.Identity) {
    $SafeLinksPolicy = New-SafeLinksPolicy -Name "Safe Links"
}

Set-SafeLinksPolicy -Identity $SafeLinksPolicy.Identity -IsEnabled $True -
ScanUrls $True -EnableForInternalSenders $True -AllowClickThrough $False
```

Default Value:

disabled

References:

1. <https://docs.microsoft.com/en-us/office365/securitycompliance/atp-safe-links>
2. <https://docs.microsoft.com/en-us/office365/securitycompliance/set-up-atp-safe-links-policies>

Notes:

ATP Safe Links features are part of Advanced Threat Protection, which is included in Office 365 Enterprise E5, Microsoft 365 Business, and Microsoft 365 Enterprise.

CIS Controls:

Version 7

7 Email and Web Browser Protections

Email and Web Browser Protections

4.7 (L2) Ensure the Advanced Threat Protection Safe Attachments policy is enabled (Scored)

Profile Applicability:

- Level 2

Description:

Enabling the Advanced Threat Protection Safe Attachments policy extends malware protections to include routing all messages and attachments without a known malware signature to a special hypervisor environment. In that environment, a behavior analysis is performed using a variety of machine learning and analysis techniques to detect malicious intent.

Rationale:

This policy increases the likelihood of identifying and stopping previously unknown malware.

Audit:

To verify the ATP Safe Attachments policy is enabled, use the Microsoft 365 Admin Center:

1. Click `Security & Compliance` to open the Security & Compliance portal.
2. Navigate to `Threat management > Policy > ATP Safe Attach.`
3. Under `Policies that apply to specific recipients`, verify that at least one policy exists.

To verify the ATP Safe Attachments policy is enabled, you can also use the Exchange Online PowerShell:

1. Connect to Exchange Online using `Connect-EXOPSSession`
2. Run the following PowerShell command:

```
Get-SafeAttachmentPolicy | where-object {$_.Enable -eq "True"}
```

Remediation:

To enable the ATP Safe Attachments policy, use the Microsoft 365 Admin Center:

1. Click `Security & Compliance` to open the Security & Compliance portal.
2. Navigate to `Threat management > Policy > ATP Safe Attach.`

3. Click +.
4. Enter Policy Name and Description.
5. Select Block, Monitor or Dynamic Delivery.
6. Select Save.

Impact:

Delivery of email with attachments may be delayed while scanning is occurring.

Default Value:

disabled

CIS Controls:

Version 7

7 Email and Web Browser Protections

Email and Web Browser Protections

4.8 (L2) Ensure basic authentication for Exchange Online is disabled (Scored)

Profile Applicability:

- Level 2

Description:

Basic authentication may allow users to access Exchange Online using legacy or unapproved email clients that do not support modern authentication mechanisms, such as multifactor authentication.

Rationale:

Disabling basic authentication prevents use of legacy and unapproved email clients with weaker authentication mechanisms that would increase the risk of email account credential compromise.

Audit:

To verify basic authentication is disabled, use the Exchange Online PowerShell Module:

1. Run the Microsoft Exchange Online PowerShell Module.
2. Connect using `Connect-EXOPSSession`.
3. Run the following PowerShell command:

```
Get-OrganizationConfig | Select-Object -ExpandProperty  
DefaultAuthenticationPolicy | ForEach { Get-AuthenticationPolicy $_ | Select-  
Object AllowBasicAuth* }
```

4. Verify each of the basic authentication types is set to `false`. If no results are shown or an error is displayed, then no default authentication policy has been defined for your organization.
5. Verify Exchange Online users are configured to use the appropriate authentication policy by running the following PowerShell command:

```
Get-User -ResultSize Unlimited | Select-Object UserPrincipalName,  
AuthenticationPolicy
```

Remediation:

To disable basic authentication, use the Exchange Online PowerShell Module:

1. Run the Microsoft Exchange Online PowerShell Module.
2. Connect using `Connect-EXOPSSession`.
3. Run the following PowerShell command:

```
$AuthenticationPolicy = Get-OrganizationConfig | Select-Object
DefaultAuthenticationPolicy

If (-not $AuthenticationPolicy.Identity) {
    $AuthenticationPolicy = New-AuthenticationPolicy "Block Basic Auth";
    Set-OrganizationConfig -DefaultAuthenticationPolicy
$AuthenticationPolicy.Identity
}

Set-AuthenticationPolicy -Identity $AuthenticationPolicy.Identity -
AllowBasicAuthActiveSync:$false -AllowBasicAuthAutodiscover:$false -
AllowBasicAuthImap:$false -AllowBasicAuthMapi:$false -
AllowBasicAuthOfflineAddressBook:$false -AllowBasicAuthOutlookService:$false -
-AllowBasicAuthPop:$false -AllowBasicAuthPowershell:$false -
AllowBasicAuthReportingWebServices:$false -AllowBasicAuthRest:$false -
AllowBasicAuthRpc:$false -AllowBasicAuthSmtpt:$false -
AllowBasicAuthWebServices:$false

Get-User -ResultSize Unlimited | ForEach-Object { Set-User -Identity
$_.Identity -AuthenticationPolicy $AuthenticationPolicy.Identity -
STSRefreshTokensValidFrom $($([System.DateTime]::UtcNow) }
```

Impact:

Blocking basic authentication will block the following legacy Exchange Online features:

- App passwords: An app password is a code that gives an app or device permission to access your Microsoft 365 account. If multi-factor authentication is enabled for your organization and you're using apps that connect to your Microsoft 365 account, you'll need to generate an app password so the app can connect to Microsoft 365. For example, if you're using Outlook 2016 or earlier with Microsoft 365, an app password is required.
- Availability address spaces: These contain a service account that's used to share calendar free/busy information in hybrid and federated deployments. The service account authenticates with a username and password, so blocking Basic authentication blocks the authentication flow.

Default Value:

false

References:

1. <https://docs.microsoft.com/en-us/exchange/clients-and-mobile-in-exchange-online/disable-basic-authentication-in-exchange-online?redirectSourcePath=%252fen-us%252farticle%252fdisable-basic-authentication-in-exchange-online-bba2059a-7242-41d0-bb3f-baaf7ec1abd7>

CIS Controls:

Version 7

7 Email and Web Browser Protections

Email and Web Browser Protections

16.3 Require Multi-factor Authentication

Require multi-factor authentication for all user accounts, on all systems, whether managed onsite or by a third-party provider.

4.9 (L1) Ensure that an anti-phishing policy has been created (Scored)

Profile Applicability:

- Level 1

Description:

By default, Office 365 includes built-in features that help protect your users from phishing attacks. Set up anti-phishing policies to increase this protection, for example by refining settings to better detect and prevent impersonation and spoofing attacks. The default policy applies to all users within the organization, and is a single view where you can fine-tune anti-phishing protection. Custom policies can be created and configured for specific users, groups or domains within the organization and will take precedence over the default policy for the scoped users.

Rationale:

Protects users from phishing attacks (like impersonation and spoofing), and uses safety tips to warn users about potentially harmful messages.

Audit:

To review the anti-phishing policy, use the Microsoft 365 Admin Center:

1. Select Security and Compliance.
2. Select Threat Management and Policy.
3. Select ATP Anti-phishing.
4. Verify a policy exists.

To verify anti-phishing policy, use the Exchange Online PowerShell Module:

1. Connect to Exchange Online service using `Connect-EXOPSSession`.
2. Run the following Exchange Online PowerShell command:

```
Get-AntiPhishPolicy | ft Name
```

3. Verify `Office365 Antiphish Default` policy exists

Remediation:

To set the anti-phishing policy, use the Microsoft 365 Admin Center:

1. Select Security and Compliance.
2. Select Threat Management and Policy.
3. Select ATP Anti-phishing.
4. Click Create to create a anti-phishing policy.

To create anti-phishing policy, use the Exchange Online PowerShell Module:

1. Connect to Exchange Online service using `Connect-EXOPSSession`.
2. Run the following Exchange Online PowerShell command:

```
New-AntiPhishPolicy -Name "Office365 AntiPhish Policy"
```

CIS Controls:

Version 7

7 Email and Web Browser Protections

Email and Web Browser Protections

4.10 (L1) Ensure that DKIM is enabled for all Exchange Online Domains (Scored)

Profile Applicability:

- Level 1

Description:

You should use DKIM in addition to SPF and DMARC to help prevent spoofers from sending messages that look like they are coming from your domain.

Rationale:

By enabling DKIM with Office 365, messages that are sent from Exchange Online will be cryptographically signed. This will allow the receiving email system to validate that the messages were generated by a server that the organization authorized and not being spoofed.

Audit:

To review if DKIM is enabled, use the Microsoft 365 Admin Center:

1. Launch the Security & Compliance Admin Center
2. Click Threat Management > Policy
3. Click DKIM
4. Click on each domain and confirm that Sign messages for this domain with DKIM signatures is Enabled.

To verify DKIM is enabled, use the Exchange Online PowerShell Module:

1. Connect to Exchange Online service using `Connect-EXOPSSession`.
2. Run the following Exchange Online PowerShell command:

```
Get-DkimSigningConfig
```

3. Verify `Enabled` is set to `True`

Remediation:

To setup DKIM records, first add the following records to your DNS system, for each domain in Exchange Online that you plan to use to send email with:

1. For each accepted domain in Exchange Online, two DNS entries are required.

```
Host name: selector1._domainkey
Points to address or value: selector1-
<domainGUID>._domainkey.<initialDomain>
TTL: 3600
Host name: selector2._domainkey
Points to address or value: selector2-
<domainGUID>._domainkey.<initialDomain>
TTL: 3600
```

For Office 365, the selectors will always be `selector1` or `selector2`.
domainGUID is the same as the domainGUID in the customized MX record for your custom domain that appears before `mail.protection.outlook.com`. For example, in the following MX record for the domain `contoso.com`, the domainGUID is `contoso-com`:

```
contoso.com. 3600 IN MX 5 contoso-com.mail.protection.outlook.com
```

`initialDomain` is the domain that you used when you signed up for Office 365. Initial domains always end in `onmicrosoft.com`.

2. After the DNS records are created, enable DKIM signing in the Office 365 Admin Portal
3. Launch the Security & Compliance Admin Center.
4. Click Threat Management > Policy.
5. Click DKIM.
6. Click on each domain and click `Enable` next to `Sign messages for this domain with DKIM signature`.

To set DKIM is enabled, use the Exchange Online PowerShell Module:

1. Connect to Exchange Online service using `Connect-EXOPSSession`.
2. Run the following Exchange Online PowerShell command:

```
Set-DkimSigningConfig -Identity < domainName > -Enabled $True
```

References:

1. <https://docs.microsoft.com/en-us/office365/SecurityCompliance/use-dkim-to-validate-outbound-email>

4.11 (L1) Ensure that SPF records are published for all Exchange Domains (Not Scored)

Profile Applicability:

- Level 1

Description:

For each domain that is configured in Exchange, a corresponding Sender Policy Framework (SPF) record should be created.

Rationale:

SPF records allow Exchange Online Protection and other mail systems know where messages from your domains are allowed to originate. This information can be used to by that system to determine how to treat the message based on if it is being spoofed or is valid.

Audit:

To verify that SPF records are published for each Exchange Online Domain, do the following:

1. Open a command prompt.
2. Type the following command:

```
nslookup -type=txt domain1.com
```

3. Ensure that a value exists and that it includes include:spf.protection.outlook.com. This designates Exchange Online as a designated sender.

Remediation:

To setup SPF records for Exchange Online accepted domains, perform the following steps:

1. If all email in your domain is sent from and received by Exchange Online, add the following TXT record for each Accepted Domain:

```
v=spf1 include:spf.protection.outlook.com -all
```

2. If there are other systems that send email in the environment, refer to this article for the proper SPF configuration: <https://docs.microsoft.com/en->

[us/office365/SecurityCompliance/set-up-spf-in-office-365-to-help-prevent-spoofing](https://docs.microsoft.com/en-us/office365/SecurityCompliance/set-up-spf-in-office-365-to-help-prevent-spoofing).

References:

1. <https://docs.microsoft.com/en-us/office365/SecurityCompliance/set-up-spf-in-office-365-to-help-prevent-spoofing>

CIS Controls:

Version 7

7 Email and Web Browser Protections

Email and Web Browser Protections

4.12 (L1) Ensure DMARC Records for all Exchange Online domains are published (Not Scored)

Profile Applicability:

- Level 1

Description:

Publish Domain-Based Message Authentication, Reporting and Conformance (DMARC) records for each Exchange Online Accepted Domain.

Rationale:

Domain-based Message Authentication, Reporting and Conformance (DMARC) work with Sender Policy Framework (SPF) and DomainKeys Identified Mail (DKIM) to authenticate mail senders and ensure that destination email systems trust messages sent from your domain.

Audit:

To verify that DMARC records are published, perform the following steps:

1. Open a command prompt.
2. For each of the Accepted Domains in Exchange Online type the following command:

```
nslookup -type=txt _dmarc.domain1.com
```

3. Ensure that a policy exists that starts with `v=DMARC1;`.

Remediation:

To add DMARC records, use the following steps:

1. For each Exchange Online Accepted Domain, add the following record to DNS:

```
Record: _dmarc.domain1.com  
Type:   TXT  
Value:  v=DMARC1; p=none;
```

2. This will create a basic DMARC policy that audits compliance

References:

1. <https://docs.microsoft.com/en-us/office365/SecurityCompliance/use-dmarc-to-validate-email#CreateDMARCRecord>

CIS Controls:

Version 7

7 Email and Web Browser Protections

Email and Web Browser Protections

4.13 (L1) Ensure notifications for internal users sending malware is Enabled (Scored)

Profile Applicability:

- Level 1

Description:

Setup the EOP malware filter to notify administrators if internal senders are blocked for sending malware.

Rationale:

This setting alerts administrators that an internal user sent a message that contained malware. This may indicate an account or machine compromise, that would need to be investigated.

Audit:

To verify notifications for internal users sending malware is enabled, use the Microsoft 365 Admin Center:

1. Launch the Security & Compliance Admin Center.
2. Go to Threat Management > Policy > Anti-malware.
3. Ensure the setting Notify administrator about undelivered messages from internal senders is checked and that there is at least one email address under Administrator email address.

To check the setting from PowerShell, use the Exchange Online Module for PowerShell

1. Connect to Exchange Online by using the `connect-exopssession` commandlet.
2. Run the following command:

```
Get-MalwareFilterPolicy | fl EnableInternalSenderAdminNotifications,  
InternalSenderAdminAddress
```

Remediation:

To enable notifications for internal users sending malware, use the Microsoft 365 Admin Center:

1. Launch the Security & Compliance Admin Center.

2. Go to Threat Management > Policy > Anti-malware.
3. Check the setting Notify administrator about undelivered messages from internal senders and enter the email address of the administrator who should be notified under Administrator email address.

To check the setting from PowerShell, use the Exchange Online Module for PowerShell

1. Connect to Exchange Online by using the `connect-exopssession` commandlet.
2. Run the following command:

```
set-MalwareFilterPolicy -EnableInternalSenderAdminNotifications $True -  
InternalSenderAdminAddress admin@domain1.com
```

CIS Controls:

Version 7

8 Malware Defenses

Malware Defenses

5 Auditing

5.1 (L1) Ensure Microsoft 365 audit log search is Enabled (Scored)

Profile Applicability:

- Level 1

Description:

When audit log search in the Microsoft 365 Security & Compliance Center is enabled, user and admin activity from your organization is recorded in the audit log and retained for 90 days. However, your organization might be using a third-party security information and event management (SIEM) application to access your auditing data. In that case, a global admin can turn off audit log search in Microsoft 365.

Rationale:

Enabling Microsoft 365 audit log search helps Office 365 back office teams to investigate activities for regular security operational or forensic purposes.

Audit:

To verify Microsoft 365 audit log search is enabled, use the Microsoft 365 Admin Center:

1. Log in as an administrator.
2. Click *Security & Compliance*.
3. In the Security & Compliance Center, navigate to *Search & investigation > Audit log search*.
4. Verify that you are able to do searches (e.g. try searching for *Activities as Accessed file* and results should be displayed).

To verify Microsoft 365 audit log search is enabled, use the Exchange Online PowerShell Module:

1. Run Microsoft Exchange Online PowerShell Module.
2. Connect using *Connect-EXOPSSession*.
3. Run the following PowerShell command:

```
Set-AdminAuditLogConfig | Select-Object -ExpandProperty  
UnifiedAuditLogIngestionEnabled
```

4. Verify the resulting value is *true*.

Remediation:

To enable Microsoft 365 audit log search, use the Microsoft 365 Admin Center:

1. Log in as an administrator.
2. Click `Security & Compliance`.
3. In the Security & Compliance Center, navigate to `Search & investigation > Audit log search`.
4. Click `Turn on auditing` next to the information warning at the top.
5. Click `Yes` on the dialog box to confirm.

To enable Microsoft 365 audit log search, use the Exchange Online PowerShell Module:

1. Run Microsoft Exchange Online PowerShell Module.
2. Connect using `Connect-EXOPSSession`.
3. Run the following PowerShell command:

```
Set-AdminAuditLogConfig -UnifiedAuditLogIngestionEnabled $true
```

A message is displayed saying that it might take up to 60 minutes for the change to take effect. If an error appears, you may need to run `Enable-OrganizationCustomization` before disconnecting and trying the command again.

Default Value:

disabled

References:

1. <https://docs.microsoft.com/en-us/office365/securitycompliance/turn-audit-log-search-on-or-off>

CIS Controls:

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

5.2 (L1) Ensure mailbox auditing for all users is Enabled (Scored)

Profile Applicability:

- Level 1

Description:

By turning on mailbox auditing, Microsoft 365 back office teams can track logons to a mailbox as well as what actions are taken while the user is logged on. After you turn on mailbox audit logging for a user mailbox, you can search the audit log for mailbox activity. Additionally, when mailbox audit logging is turned on, some actions performed by administrators, delegates, and owners are logged by default.

Rationale:

Whether it is for regulatory compliance or for tracking unauthorized configuration changes in Microsoft 365, enabling mailbox auditing allows for Microsoft 365 backoffice teams to run security operations, forensics or general investigations on mailbox activities.

Audit:

To verify mailbox auditing is enabled for all users, use the Exchange Online PowerShell Module:

1. Run Microsoft Exchange Online PowerShell Module.
2. Connect using `Connect-EXOPSSession`.
3. Run the following PowerShell command:

```
Get-Mailbox -ResultSize Unlimited -Filter {RecipientTypeDetails -eq "UserMailbox"} | Format-Table Name, AuditEnabled
```

4. Verify `AuditEnabled` is set to `True` for all mailboxes.

Remediation:

To enable mailbox auditing for all users, use the Exchange Online PowerShell Module:

1. Run Microsoft Exchange Online PowerShell Module.
2. Connect using `Connect-EXOPSSession`.
3. Run the following PowerShell commands:

```
$AuditAdmin = @("Copy", "Create", "FolderBind",  
"HardDelete", "MessageBind", "Move", "MoveToDeletedItems", "SendAs",
```

```
"SendOnBehalf", "SoftDelete", "Update", "UpdateCalendarDelegation",  
"UpdateFolderPermissions", "UpdateInboxRules")  
  
$AuditDelegate =  
@("Create", "FolderBind", "HardDelete", "Move", "MoveToDeletedItems", "SendAs",  
"SendOnBehalf", "SoftDelete", "Update", "UpdateFolderPermissions", "Update  
InboxRules")  
  
$AdminOwner =  
@("Create", "HardDelete", "MailboxLogin", "Move", "MoveToDeletedItems", "Soft  
Delete", "Update", "UpdateCalendarDelegation",  
"UpdateFolderPermissions", "UpdateInboxRules")  
  
Get-Mailbox -ResultSize Unlimited -Filter {RecipientTypeDetails -eq  
"UserMailbox" -or RecipientTypeDetails -eq "SharedMailbox" -or  
RecipientTypeDetails -eq "RoomMailbox" -or RecipientTypeDetails -eq  
"DiscoveryMailbox"} | Set-Mailbox -AuditEnabled $true -AuditLogAgeLimit 180 -  
AuditAdmin $AuditAdmin -AuditDelegate $AuditDelegate -AuditOwner $AuditOwner
```

Default Value:

disabled

References:

1. <https://docs.microsoft.com/en-us/office365/securitycompliance/enable-mailbox-auditing>

CIS Controls:

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

5.3 (L1) Ensure the Azure AD 'Risky sign-ins' report is reviewed at least weekly (Not Scored)

Profile Applicability:

- Level 1

Description:

This report contains records of accounts that have had activity that could indicate they are compromised, such as accounts that have: -successfully signed in after multiple failures, which is an indication that the accounts have cracked passwords -signed in to your tenancy from a client IP address that has been recognized by Microsoft as an anonymous proxy IP address (such as a TOR network) -successful signins from users where two signins appeared to originate from different regions and the time between signins makes it impossible for the user to have traveled between those regions

Rationale:

Reviewing this report on a regular basis allows for identification and remediation of compromised accounts.

Audit:

To verify the report is being reviewed at least weekly, confirm that the necessary procedures are in place and being followed.

Remediation:

To review the report, perform the following steps using the Azure Portal:

1. Go to portal.azure.com.
2. Click `Azure Active Directory`.
3. Select `Risky Sign-ins`.
4. Review by `Detection Type`.

To get risky sign-ins event report programatically, use following graph API:

```
https://graph.microsoft.com/beta/identityRiskEvents?$filter=riskEventDateTime  
gt < 7 days older datetime > and riskEventStatus eq 'active'
```

References:

1. <https://docs.microsoft.com/en-us/azure/active-directory/reports-monitoring/concept-user-at-risk>
2. <https://docs.microsoft.com/en-us/azure/active-directory/reports-monitoring/howto-remediate-users-flagged-for-risk>

CIS Controls:

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

5.4 (L2) Ensure the Application Usage report is reviewed at least weekly (Not Scored)

Profile Applicability:

- Level 2

Description:

You should review the Application Usage report at least weekly. This report includes a usage summary for all Software As A Service (SaaS) applications that are integrated with your directory.

Rationale:

Review the list of app registrations on a regular basis to look for risky apps that users have enabled that could cause data spillage or accidental elevation of privilege. Attackers can often get access to data illicitly through third-party SaaS applications.

Audit:

To verify the report is being reviewed at least weekly, confirm that the necessary procedures are in place and being followed.

Remediation:

To review the report, perform the following steps using the Azure Portal:

1. Go to portal.azure.com.
2. Click `Azure Active Directory`.
3. Select `App Registrations`.
4. Review the information.

CIS Controls:

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

5.5 (L1) Ensure the self-service password reset activity report is reviewed at least weekly (Not Scored)

Profile Applicability:

- Level 1

Description:

The Microsoft 365 platforms allow a user to reset their password in the event they forget it. The self-service password reset activity report logs each time a user successfully resets their password this way. You should review the self-service password reset activity report at least weekly.

Rationale:

An attacker will commonly compromise an account, then change the password to something they control and can manage.

Audit:

To verify the report is being reviewed at least weekly, confirm that the necessary procedures are in place and being followed.

Remediation:

To review the report, perform the following steps using the Azure Portal:

1. Go to portal.azure.com.
2. Go to 'Azure Active Directory'.
3. Click on 'Password Reset'.
4. Select 'Audit Logs'.
5. Review the list of users who have reset their passwords in the last seven days.

CIS Controls:

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

5.6 (L1) Ensure user role group changes are reviewed at least weekly (Not Scored)

Profile Applicability:

- Level 1

Description:

User role group changes should be reviewed on a weekly basis to ensure no one has been improperly added to an administrative role.

Rationale:

Illicit role group changes could give an attacker elevated privileges to perform more dangerous and impactful things in your tenancy.

Audit:

To verify user role group changes are being reviewed at least weekly, confirm that the necessary procedures are in place and being followed.

Remediation:

To review user role group changes, perform the following steps using the Microsoft 365 Admin Center:

1. Go to Security and Compliance Center.
2. Select Search and Investigation and then Audit Log Search.
3. Set Activities to Added member to role.
4. Set Start Date and End Date.
5. Click Search.
6. Review.

To review user role group changes, perform the following steps using Exchange Online PowerShell Module:

1. Connect to Exchange Online using `Connect-EXOPSSession`.
2. Run the following Exchange Online PowerShell command:

```
$startDate = (([datetime]$ed).AddDays(-7)).ToShortDateString()
$endDate = (Get-date).ToShortDateString()

Search-UnifiedAuditLog -StartDate $startDate -EndDate $endDate | Where-Object
{ $_.Operations -eq "Add member to role." }
```

3. Review the output

CIS Controls:

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

5.7 (L1) Ensure mail forwarding rules are reviewed at least weekly (Not Scored)

Profile Applicability:

- Level 1

Description:

You should review mail forwarding rules to external domains at least every week.

Rationale:

While there are lots of legitimate uses of mail forwarding rules, they are also a popular data exfiltration tactic for attackers. You should review them regularly to ensure your users' email is not being exfiltrated.

Audit:

To verify mail forwarding rules are being reviewed at least weekly, confirm that the necessary procedures are in place and being followed.

Remediation:

To review mail forwarding rules, use the Microsoft 365 Admin Center:

1. Go to Security and Compliance Center.
2. Select Mail Flow and then Dashboard.
3. Review Auto Forwarded Messages on the dashboard.

To review mail forwarding rules, use the following Powershell script:

Uses the administrator user credential to export Mail forwarding rules, User Delegates and SMTP Forwarding policies to multiple csv files

```
import-module MSOnline

#Let's get us an admin cred!
$userCredential = Get-Credential

#This connects to Azure Active Directory
Connect-MsolService -Credential $userCredential

$exoSession = New-PSSession -ConfigurationName Microsoft.Exchange -
ConnectionUri https://outlook.office365.com/powershell-liveid/ -Credential
$userCredential -Authentication Basic -AllowRedirection
Import-PSSession $exoSession
```

```

$allUsers = @()
$AllUsers = Get-MsolUser -All -EnabledFilter EnabledOnly | select ObjectID,
UserPrincipalName, FirstName, LastName, StrongAuthenticationRequirements,
StsRefreshTokensValidFrom, StrongPasswordRequired,
LastPasswordChangeTimestamp | Where-Object {($_.UserPrincipalName -notlike
"*#EXT#")}

$UserInboxRules = @()
$UserDelegates = @()

foreach ($User in $allUsers)
{
    Write-Host "Checking inbox rules and delegates for user: "
$User.UserPrincipalName;
    $UserInboxRules += Get-InboxRule -Mailbox $User.UserPrincipalname |
Select Name, Description, Enabled, Priority, ForwardTo,
ForwardAsAttachmentTo, RedirectTo, DeleteMessage | Where-Object
{($_.ForwardTo -ne $null) -or ($_.ForwardAsAttachmentTo -ne $null) -or
($_.RedirectsTo -ne $null)}
    $UserDelegates += Get-MailboxPermission -Identity $User.UserPrincipalName
| Where-Object {($_.IsInherited -ne "True") -and ($_.User -notlike "*SELF*")}
}

$SMTPForwarding = Get-Mailbox -ResultSize Unlimited | select
DisplayName,ForwardingAddress,ForwardingSMTPAddress,DeliverToMailboxandForwar
d | where {$_ .ForwardingSMTPAddress -ne $null}

# Export list of inboxRules, Delegates and SMTP Forwards
$UserInboxRules | Export-Csv MailForwardingRulesToExternalDomains.csv
$UserDelegates | Export-Csv MailboxDelegatePermissions.csv
$SMTPForwarding | Export-Csv Mailboxsmtpforwarding.csv

```

CIS Controls:

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

5.8 (L1) Ensure the Mailbox Access by Non-Owners Report is reviewed at least biweekly (Not Scored)

Profile Applicability:

- Level 1

Description:

You should review the Mailbox Access by Non-Owners report at least every other week. This report shows which mailboxes have been accessed by someone other than the mailbox owner.

Rationale:

While there are many legitimate uses of delegate permissions, regularly reviewing that access can help prevent an external attacker from maintaining access for a long time, and can help discover malicious insider activity sooner.

Audit:

To verify the report is being reviewed at least biweekly, confirm that the necessary procedures are in place and being followed.

Remediation:

To review the report, perform the following steps using the Microsoft 365 Admin Center:

1. Click `Exchange`.
2. Click `Compliance Management`.
3. Select `Run a non-owner mailbox access report`.
4. Enter `Start Date` and `End Date`.
5. Change `Search for access by field` to `all non-owners`.
6. Select `Search`.

CIS Controls:

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

5.9 (L1) Ensure the Malware Detections report is reviewed at least weekly (Not Scored)

Profile Applicability:

- Level 1

Description:

You should review the Malware Detections report at least weekly. This report shows specific instances of Microsoft blocking a malware attachment from reaching your users.

Rationale:

While this report isn't strictly actionable, reviewing it will give you a sense of the overall volume of malware being targeted at your users, which may prompt you to adopt more aggressive malware mitigations.

Audit:

To verify the report is being reviewed at least weekly, confirm that the necessary procedures are in place and being followed.

Remediation:

To review the report, use the Microsoft 365 Admin Center:

1. Select `Security and Compliance`.
2. Select `Report and Dashboard`.
3. Review the `Malware Detected in Email` report.

CIS Controls:

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

5.10 (L1) Ensure the Account Provisioning Activity report is reviewed at least weekly (Not Scored)

Profile Applicability:

- Level 1

Description:

The Account Provisioning Activity report details any account provisioning that was attempted by an external application.

Rationale:

If you don't usually use a third party provider to manage accounts, any entry on the list is likely illicit. If you do, this is a great way to monitor transaction volumes and look for new or unusual third party applications that are managing users. If you see something unusual, contact the provider to determine if the action is legitimate.

Audit:

To verify the report is being reviewed at least weekly, confirm that the necessary procedures are in place and being followed.

Remediation:

To review the report, use the Microsoft 365 Admin Center:

1. Go to Security and Compliance Center.
2. Select Search and Investigation and then Audit Log Search.
3. Set Activities to Added user.
4. Set Start Date and End Date.
5. Click Search.
6. Review.

To review Account Provisioning Activity report, use the Exchange Online PowerShell Module:

1. Connect to Exchange Online service using `Connect-EXOPSSession`.
2. Run the following Exchange Online PowerShell command:

```
$startDate = ([datetime]$ed).AddDays(-7).ToShortDateString()  
$endDate = (Get-date).ToShortDateString()
```

```
Search-UnifiedAuditLog -StartDate $startDate -EndDate $endDate | Where-Object  
{ $_.Operations -eq "add user." }
```

3. Review the output

CIS Controls:

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

5.11 (L1) Ensure non-global administrator role group assignments are reviewed at least weekly (Not Scored)

Profile Applicability:

- Level 1

Description:

You should review non-global administrator role group assignments at least every week.

Rationale:

While these roles are less powerful than a global admin, they do grant special privileges that can be used illicitly. If you see something unusual, contact the user to confirm it is a legitimate need.

Audit:

To verify non-global administrator role group assignments are being reviewed at least weekly, confirm that the necessary procedures are in place and being followed.

Remediation:

To review non-global administrator role group assignments, use the Microsoft 365 Admin Center:

1. Go to Security and Compliance Center.
2. Select Search and Investigation and then Audit Log Search.
3. Set Initiated by (Actor) to the name of a non-global admin.
4. Set Start Date and End Date.
5. Click Search.
6. Review.

CIS Controls:

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

5.12 (L1) Ensure the spoofed domains report is review weekly (Not Scored)

Profile Applicability:

- Level 1

Description:

Use spoof intelligence in the Security & Compliance Center on the Anti-spam settings page to review all senders who are spoofing either domains that are part of your organization, or spoofing external domains. Spoof intelligence is available as part of Office 365 Enterprise E5 or separately as part of Advanced Threat Protection (ATP) and as of October, 2018 Exchange Online Protection (EOP).

Rationale:

Bad actors spoof domains to trick users into conducting actions they normally would not or should not via phishing emails.

Audit:

To verify the report is being reviewed at least weekly, confirm that the necessary procedures are in place and being followed.

Remediation:

To review the report, use the Microsoft 365 Admin Center:

1. Go to Security and Compliance Center.
2. Select Threat Management and then Dashboard.
3. Click Spoofed domains that failed authentication over the past 30 days.
4. Review.

To verify mailbox auditing is enabled for all users, use the Exchange Online PowerShell Module:

1. Connect to Exchange Online using `Connect-EXOPSSession`.
2. Run the following PowerShell command:

```
Get-PhishFilterPolicy -Detailed -SpoofAllowBlockList -SpoofType Internal
```

3. Review.

5.13 (L2) Ensure Microsoft 365 Cloud App Security is Enabled (Not Scored)

Profile Applicability:

- Level 2

Description:

Enabling Microsoft 365 Cloud App Security gives you insight into suspicious activity in Microsoft 365 so you can investigate situations that are potentially problematic and, if needed, take action to address security issues.

Rationale:

You can receive notifications of triggered alerts for atypical or suspicious activities, see how your organization's data in Microsoft 365 is accessed and used, suspend user accounts exhibiting suspicious activity, and require users to log back in to Microsoft 365 apps after an alert has been triggered.

Audit:

To verify Microsoft 365 Cloud App Security is enabled, use the Microsoft 365 Admin Center:

1. Select `Security and Compliance`.
2. Select `Alerts`.
3. Select `Manage advanced alerts`.
4. Verify that `Turn on Microsoft 365 Cloud App Security` is selected.

To verify Microsoft 365 Cloud App Security is enabled, use the Microsoft 365 SecureScore Portal:

1. Login to Microsoft 365 SecureScore portal (<https://seurescore.microsoft.com>) using admin permissions (global admin or a custom admin role) for an Office 365 Enterprise, Microsoft 365 Business, or Office 365 Business Premium subscription.
2. Click on `Enable Cloud App Security Console` policy to see the status of the Microsoft 365 Cloud App Security console.

To verify Microsoft 365 Cloud App Security is enabled, use the Microsoft 365 SecureScore REST API:

```
GET https://graph.microsoft.com/beta/security/secureScores
```

Remediation:

To enable Microsoft 365 Cloud App Security, use the Microsoft 365 Admin Center:

1. **Select** Security and Compliance.
2. **Select** Alerts.
3. **Select** Manage advanced alerts.
4. **Check** Turn on Microsoft 365 Cloud App Security.
5. **Click** Go to Microsoft 365 Cloud App Security.

5.14 (L1) Ensure the report of users who have had their email privileges restricted due to spamming is reviewed (Not Scored)

Profile Applicability:

- Level 1

Description:

Review and unblock users who have been blocked for sending too many messages marked as spam/bulk.

Rationale:

Users who are found on the restricted users list have a high probability of having been compromised. Review of this list will allow an organization to remediate these user accounts, and then unblock them.

Audit:

To verify the report is being reviewed at least weekly, confirm that the necessary procedures are in place and being followed.

Remediation:

To review the report, use the Microsoft 365 Admin Center:

1. Select `Security and Compliance`.
2. Select `Threat Management and Review`.
3. Click 'Restricted Users'.
4. Review alerts and take appropriate action (unblocking) after account has been remediated.

CIS Controls:

Version 7

6.2 Activate audit logging

Ensure that local logging has been enabled on all systems and networking devices.

6 Storage

6.1 (L2) Ensure document sharing is being controlled by domains with whitelist or blacklist (Scored)

Profile Applicability:

- Level 2

Description:

You should control sharing of documents to external domains by either blocking domains or only allowing sharing with specific named domains.

Rationale:

Attackers will often attempt to expose sensitive information to external entities through sharing, and restricting the domains that your users can share documents with will reduce that surface area.

Audit:

To verify document sharing settings, use the Microsoft 365 Admin Center:

1. Navigate to Microsoft 365 administration portal (<https://admin.microsoft.com>), Click on Admin Centers and then SharePoint.
2. Click Sharing.
3. Confirm that Limit external sharing using domains is checked.
4. Verify that Allow sharing only with users from these domains or Don't allow sharing with users from these blocked domains is set correctly along with an accurate list of approved or disallowed domains.

To verify document sharing setting, you can also use SharePoint Online PowerShell:

1. Connect to SharePoint Online using Connect-SPOService
2. Run the following PowerShell command:

```
Get-SPOTenant | fl SharingDomainRestrictionMode,SharingAllowedDomainList
```

Remediation:

To configure document sharing restrictions, use the Microsoft 365 Admin Center:

1. Select Admin Centers and SharePoint.

2. Click Sharing.
3. Check Limit external sharing using domains.
4. Toggle Allow sharing only with users from these domains **or** Don't allow sharing with users from these blocked domains.
5. Enter list of approved or disallowed domains.

To configure document sharing restrictions, you can also use SharePoint Online PowerShell:

1. Connect to SharePoint Online using Connect-SPOService
2. Run the following PowerShell command:

```
Set-SPTenant -SharingDomainRestrictionMode AllowList -  
SharingAllowedDomainList "domain1.com domain2.com"
```

Default Value:

off

CIS Controls:

Version 7

13 Data Protection

Data Protection

6.2 (L1) Ensure expiration time for external sharing links is set (Scored)

Profile Applicability:

- Level 1

Description:

You should restrict the length of time that anonymous access links are valid.

Rationale:

An attacker can compromise a user account for a short period of time, send anonymous sharing links to an external account, then take their time accessing the data. They can also compromise external accounts and steal the anonymous sharing links sent to those external entities well after the data has been shared. Restricting how long the links are valid can reduce the window of opportunity for attackers.

Audit:

To verify anonymous access links are correctly set to expire, use the Microsoft 365 Admin Center:

1. Select `Admin Centers` and `SharePoint`.
2. Click `Sharing`.
3. Click `Anonymous access links expire in this many days`.
4. Confirm the number of days is set to the desired value, such as 30.

To verify anonymous links are correctly set to expire, you can also use SharePoint Online PowerShell:

1. Connect to SharePoint Online using `Connect-SPOService`
2. Run the following PowerShell command:

```
Get-SPOTenant | fl RequireAnonymousLinksExpireInDays
```

Remediation:

To set expiration for anonymous access links, use the Microsoft 365 Admin Center

1. Select `Admin Centers` and `SharePoint`.
2. Click `Sharing`.
3. Check `Anonymous access links expire in this many days`.
4. Set to the desired number of days, such as 30.

5. Click OK.

To set expiration for anonymous access links, you can also use SharePoint Online PowerShell:

1. Connect to SharePoint Online using Connect-SPOService
2. Run the following PowerShell command:

```
set-SPOTenant -RequireAnonymousLinksExpireInDays 30
```

Default Value:

off

CIS Controls:

Version 7

13 Data Protection

Data Protection

7 Mobile Device Management

7.1 (L1) Ensure mobile device management policies are set to require advanced security configurations to protect from basic internet attacks (Scored)

Profile Applicability:

- Level 1

Description:

You should configure your mobile device management policies to require advanced security configurations. If you do not require this, users will be able to connect from devices that are vulnerable to basic internet attacks, leading to potential breaches of accounts and data.

Rationale:

Managing mobile devices in your organization, helps provide a basic level of security to protect against attacks from these platforms. For example ensure that the device is up to date on patches or is not rooted. These configurations open those devices to vulnerabilities that are addressed in patched versions of the mobile OS.

Audit:

To verify mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Policy`.
3. Ensure a Policy exist.

Remediation:

To set mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Policy`.
3. Click `Create Policy`.

Impact:

This change will have a moderate impact on your users.

CIS Controls:

Version 7

5 Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

7.2 (L1) Ensure that mobile device password reuse is prohibited (Scored)

Profile Applicability:

- Level 1

Description:

You should not allow your users to reuse the same password on their mobile devices.

Rationale:

Devices without this protection are vulnerable to being accessed by attackers who can then steal account credentials, data, or install malware on the device.

Audit:

To verify mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profile`.
3. Select `current Profile`.
4. Select `Properties and Settings`.
5. Select `System Security`.
6. Verify `Number of previous passwords to prevent reuse` is set to 5.

Remediation:

To set mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profile`.
3. Select `current profile`.
4. Select `Properties and Settings`.
5. Select `System Security`.
6. Set `Number of previous passwords to prevent reuse` to 5.
7. Click `OK`.

Impact:

This change will have a moderate user impact

Default Value:

Password reuse is not enforced by default.

CIS Controls:

Version 7

5 Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

7.3 (L1) Ensure that mobile devices are set to never expire passwords (Scored)

Profile Applicability:

- Level 1

Description:

Ensure that users passwords on their mobile devices, never expire.

Rationale:

While this is not the most intuitive recommendation, research has found that when periodic password resets are enforced, passwords become weaker as users tend to pick something weaker and then use a pattern of it for rotation. If a user creates a strong password: long, complex and without any pragmatic words present, it should remain just as strong is 60 days as it is today. It is Microsoft's official security position to not expire passwords periodically without a specific reason.

Audit:

To verify mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profiles`.
3. Select current profile.
4. Select `Properties and Settings`.
5. Select `System Security`.
6. Ensure `Password expiration (days)` is set to 0.

Remediation:

To set mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profile`.
3. Select current profile.
4. Select `Properties and Settings`.
5. Select `System Security`.
6. Set `Password expiration (days)` to 0.
7. Click `OK`.

Impact:

This setting should not cause a noticeable impact to users

Default Value:

Password changes are not required by default

CIS Controls:

Version 7

5 Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

7.4 (L1) Ensure that users cannot connect from devices that are jail broken or rooted (Scored)

Profile Applicability:

- Level 1

Description:

You should not allow your users to use to connect with mobile devices that have been jail broken or rooted.

Rationale:

These devices have had basic protections disabled to run software that is often malicious and could very easily lead to an account or data breach.

Audit:

To verify mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Policy`.
3. Select current policy.
4. Select `Properties and Settings`.
5. Select `Device Health`.
6. Ensure `Jailbroken Devices` is set to `Blocked`.

Remediation:

To set mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Policy`.
3. Select current policy.
4. Select `Properties and Settings`.
5. Select `Device Health`.
6. Set `Jailbroken Devices` to `Blocked`.
7. Click `OK`.

CIS Controls:

Version 7

5 Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

Secure Configuration for Hardware and Software on Mobile Devices, Laptops,
Workstations and Servers

7.5 (L2) Ensure mobile devices are set to wipe on multiple sign-in failures to prevent brute force compromise (Scored)

Profile Applicability:

- Level 2

Description:

Require mobile devices to wipe on multiple sign-in failures

Rationale:

Devices without this protection are vulnerable to being accessed physically by attackers who can then steal account credentials, data, or install malware on the device.

Audit:

To verify mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profiles`.
3. Select **current profile**.
4. Select `Properties and Settings`.
5. Select `Password`.
6. Ensure `Number of sign-in failures before wiping device` is set to 10.

Remediation:

To set mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profiles`.
3. Select **current profile**.
4. Select `Properties and Settings`.
5. Select `Password`.
6. Set `Number of sign-in failures before wiping device` to 10.
7. Click `OK`.

Impact:

This setting has no impact, unless a user mistypes their password multiple times and causes their device to wipe. In that case, it will have a high user impact.

Default Value:

The default is to not wipe the device on multiple failed attempts.

CIS Controls:

Version 7

5 Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

7.6 (L1) Ensure that mobile devices require a complex password to prevent brute force attacks (Scored)

Profile Applicability:

- Level 1

Description:

You should require your users to use a complex password with a minimum password length of at least six characters to unlock their mobile devices.

Rationale:

Devices without this protection are vulnerable to being accessed physically by attackers who can then steal account credentials, data, or install malware on the device.

Audit:

To verify mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profiles`.
3. Select current profile.
4. Select `Properties and Settings`.
5. Select `Password`.
6. Ensure `Minimum password length` is set to 6.

Remediation:

To set mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profiles`.
3. Select current profile.
4. Select `Properties and Settings`.
5. Select `Password`.
6. Set `Minimum password length` to 6.
7. Click `OK`.

Impact:

This change has a moderate user impact

Default Value:

Minimum password lengths are not enforced by default

CIS Controls:

Version 7

5 Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

7.7 (L1) Ensure that settings are enable to lock multiple devices after a period of inactivity to prevent unauthorized access (Scored)

Profile Applicability:

- Level 1

Description:

You should require your users to configure their mobile devices to lock on inactivity.

Rationale:

Attackers can steal unlocked devices and access data and account information.

Audit:

To verify mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profiles`.
3. Select `current profile`.
4. Select `Properties and Settings`.
5. Select `Password`.
6. Ensure `Maximum minutes of inactivity until screen lock is set to 5`.

Remediation:

To set mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profiles`.
3. Select `current profile`.
4. Select `Properties and Settings`.
5. Select `Password`.
6. Set `Maximum minutes of inactivity until screen lock to 5`.
7. Click `OK`.

Impact:

This setting has a low impact on users.

Default Value:

Screen locking is not enabled by default.

CIS Controls:

Version 7

5 Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

7.8 (L1) Ensure that mobile device encryption is enabled to prevent unauthorized access to mobile data (Scored)

Profile Applicability:

- Level 1

Description:

You should require your users to use encryption on their mobile devices.

Rationale:

Unencrypted devices can be stolen and their data extracted by an attacker very easily.

Audit:

To verify mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profiles`.
3. Select an Android profile.
4. Select `Properties and Settings`.
5. Select `Password`.
6. Verify the value for `Encryption` is set to `Enabled`.

Remediation:

To set mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profiles`.
3. Select an Android profile.
4. Select `Properties and Settings`.
5. Select `Password`.
6. Set the value for `Encryption` to `Enabled`.
7. Click `OK`.

Impact:

This setting should have no user impact, provided the device supports the feature.

Default Value:

Device encryption is not required by the O365 platform by default, although some mobile platforms are encrypted by default.

CIS Controls:

Version 7

5 Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

7.9 (L1) Ensure that mobile devices require complex passwords to prevent brute force attacks (Scored)

Profile Applicability:

- Level 1

Description:

You should require your users to use a complex password with at least two character sets (letters and numbers, for example) to unlock their mobile devices.

Rationale:

Devices without this protection are vulnerable to being accessed physically by attackers who can then steal account credentials, data, or install malware on the device.

Audit:

To verify mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profiles`.
3. Select an iOS or Android profile.
4. Select `Properties and Settings`.
5. Select `Password`.
6. Verify the value for `Required password type` is set to `Alphanumeric`.

Remediation:

To set mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profiles`.
3. Select an iOS or Android profile.
4. Select `Properties and Settings`.
5. Select `Password`.
6. Set the value for `Required password type` to `Alphanumeric`.
7. Click `OK`.

Impact:

This setting will have a moderate user impact

Default Value:

This setting is not enabled by default.

CIS Controls:

Version 7

5 Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

7.10 (L1) Ensure that mobile devices require complex passwords to prevent brute force attacks (Scored)

Profile Applicability:

- Level 1

Description:

You should require your users to use a complex password to unlock their mobile devices.

Rationale:

Devices without this protection are vulnerable to being accessed physically by attackers who can then steal account credentials, data, or install malware on the device.

Audit:

To verify mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profiles`.
3. Select an iOS or Android profile.
4. Select `Properties and Settings`.
5. Select `Password`.
6. Verify the value for `Simple Passwords` is set to `Blocked`.

Remediation:

To set mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profiles`.
3. Select an iOS or Android profile.
4. Select `Properties and Settings`.
5. Select `Password`.
6. Set the value for `Simple Passwords` to `Blocked`.
7. Click `OK`.

Impact:

This has a moderate impact on users

Default Value:

This setting is not enabled by default

CIS Controls:

Version 7

5 Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

7.11 (L1) Ensure that devices connecting have AV and a local firewall enabled (Scored)

Profile Applicability:

- Level 1

Description:

You should configure your mobile device management policies to require the PC to have anti-virus and have a firewall enabled.

Rationale:

If you do not require this, users will be able to connect from devices that are vulnerable to basic internet attacks, leading to potential breaches of accounts and data.

Audit:

To verify mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Policy`.
3. Select an PC policy.
4. Select `Properties and Settings`.
5. Select `System Security`.
6. Verify the value for `Firewall, Antivirus, and Antispyware` are set to `Require`.

Remediation:

To set mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Policy`.
3. Select an PC policy.
4. Select `Properties and Settings`.
5. Select `System Security`.
6. Set the value for `Firewall, Antivirus, and Antispyware` to `Require`.
7. Click `OK`.

7.12 (L1) Ensure mobile device management policies are required for email profiles (Scored)

Profile Applicability:

- Level 1

Description:

You should configure your mobile device management policies to require the policy to manage the email profile of the user.

Rationale:

If you do not require this, users will be able to setup and configure email accounts without the protections of the mobile device management policy, leading to potential breaches of accounts and data.

Audit:

To verify mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profile`.
3. Select an iOS profile.
4. Select `Properties and Settings`.
5. Select `Email`.
6. Verify the value for `Require mobile devices to have a managed email profile` is set to `Require`.

Remediation:

To set mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Profile`.
3. Select an iOS profile.
4. Select `Properties and Settings`.
5. Select `Email`.
6. Set the value for `Require mobile devices to have a managed email profile` to `Require`.
7. Click `OK`.

Impact:

This setting will have a moderate impact on users

Default Value:

This setting is not enabled by default

CIS Controls:

Version 7

5 Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

7.13 (L1) Ensure mobile devices require the use of a password (Scored)

Profile Applicability:

- Level 1

Description:

You should require your users to use a password to unlock their mobile devices.

Rationale:

Devices without this protection are vulnerable to being accessed physically by attackers who can then steal account credentials, data, or install malware on the device.

Audit:

To verify mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Policy`.
3. Select an iOS policy.
4. Select `Properties and Settings`.
5. Select `Password`.
6. Verify the value for `Password` is set to `Require`.

Remediation:

To set mobile device management policies, use the Microsoft 365 Admin Center:

1. Select `inTune`.
2. Select `Policy`.
3. Select an iOS policy.
4. Select `Properties and Settings`.
5. Select `Password`.
6. Set the value for `Password` to `Require`.
7. Click `OK`.

Impact:

This change will require users to provide a password to unlock their mobile device after the timeout period expires

Default Value:

This setting is not enabled by default.

CIS Controls:

Version 7

5 Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

Secure Configuration for Hardware and Software on Mobile Devices, Laptops, Workstations and Servers

Appendix: Summary Table

Control		Set Correctly	
		Yes	No
1.1	(L1) Ensure multifactor authentication is enabled for all users in administrative roles (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.2	(L2) Ensure multifactor authentication is enabled for all users in all roles (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.3	(L1) Ensure that between two and four global admins are designated (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.4	(L1) Ensure self-service password reset is enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.5	(L1) Ensure modern authentication for Exchange Online is enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.6	(L1) Ensure modern authentication for SharePoint applications is required (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.7	(L1) Ensure modern authentication for Skype for Business Online is enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
1.8	(L1) Ensure that Office 365 Passwords Are Not Set to Expire (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
2	Application Permissions		
2.1	(L2) Ensure third party integrated applications are not allowed (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
2.2	(L2) Ensure calendar details sharing with external users is disabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
2.3	(L2) Ensure O365 ATP SafeLinks for Office Applications is Enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
2.4	(L2) Ensure Office 365 ATP for SharePoint, OneDrive, and Microsoft Teams is Enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
3	Data Management		
3.1	(L2) Ensure the customer lockbox feature is enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
3.2	(L2) Ensure SharePoint Online data classification policies are set up and used (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
3.3	(L2) Ensure external domains are not allowed in Skype or Teams (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
3.4	(L1) Ensure DLP policies are enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
3.5	(L2) Ensure that external users cannot share files, folders, and sites they do not own (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
3.6	(L2) Ensure external file sharing in Teams is enabled for only approved cloud storage services (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
4	Email Security / Exchange Online		
4.1	(L1) Ensure the Common Attachment Types Filter is enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>

4.2	(L1) Ensure Exchange Online Spam Policies are set correctly (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
4.3	(L1) Ensure mail transport rules do not forward email to external domains (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
4.4	(L1) Ensure mail transport rules do not whitelist specific domains (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
4.5	(L2) Ensure the Client Rules Forwarding Block is enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
4.6	(L2) Ensure the Advanced Threat Protection Safe Links policy is enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
4.7	(L2) Ensure the Advanced Threat Protection Safe Attachments policy is enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
4.8	(L2) Ensure basic authentication for Exchange Online is disabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
4.9	(L1) Ensure that an anti-phishing policy has been created (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
4.10	(L1) Ensure that DKIM is enabled for all Exchange Online Domains (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
4.11	(L1) Ensure that SPF records are published for all Exchange Domains (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
4.12	(L1) Ensure DMARC Records for all Exchange Online domains are published (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
4.13	(L1) Ensure notifications for internal users sending malware is Enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
5	Auditing		
5.1	(L1) Ensure Microsoft 365 audit log search is Enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
5.2	(L1) Ensure mailbox auditing for all users is Enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
5.3	(L1) Ensure the Azure AD 'Risky sign-ins' report is reviewed at least weekly (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
5.4	(L2) Ensure the Application Usage report is reviewed at least weekly (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
5.5	(L1) Ensure the self-service password reset activity report is reviewed at least weekly (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
5.6	(L1) Ensure user role group changes are reviewed at least weekly (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
5.7	(L1) Ensure mail forwarding rules are reviewed at least weekly (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
5.8	(L1) Ensure the Mailbox Access by Non-Owners Report is reviewed at least biweekly (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
5.9	(L1) Ensure the Malware Detections report is reviewed at least weekly (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
5.10	(L1) Ensure the Account Provisioning Activity report is reviewed at least weekly (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>

5.11	(L1) Ensure non-global administrator role group assignments are reviewed at least weekly (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
5.12	(L1) Ensure the spoofed domains report is review weekly (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
5.13	(L2) Ensure Microsoft 365 Cloud App Security is Enabled (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
5.14	(L1) Ensure the report of users who have had their email privileges restricted due to spamming is reviewed (Not Scored)	<input type="checkbox"/>	<input type="checkbox"/>
6	Storage		
6.1	(L2) Ensure document sharing is being controlled by domains with whitelist or blacklist (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
6.2	(L1) Ensure expiration time for external sharing links is set (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
7	Mobile Device Management		
7.1	(L1) Ensure mobile device management polices are set to require advanced security configurations to protect from basic internet attacks (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
7.2	(L1) Ensure that mobile device password reuse is prohibited (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
7.3	(L1) Ensure that mobile devices are set to never expire passwords (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
7.4	(L1) Ensure that users cannot connect from devices that are jail broken or rooted (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
7.5	(L2) Ensure mobile devices are set to wipe on multiple sign-in failures to prevent brute force compromise (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
7.6	(L1) Ensure that mobile devices require a complex password to prevent brute force attacks (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
7.7	(L1) Ensure that settings are enable to lock multiple devices after a period of inactivity to prevent unauthorized access (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
7.8	(L1) Ensure that mobile device encryption is enabled to prevent unauthorized access to mobile data (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
7.9	(L1) Ensure that mobile devices require complex passwords to prevent brute force attacks (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
7.10	(L1) Ensure that mobile devices require complex passwords to prevent brute force attacks (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
7.11	(L1) Ensure that devices connecting have AV and a local firewall enabled (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
7.12	(L1) Ensure mobile device management policies are required for email profiles (Scored)	<input type="checkbox"/>	<input type="checkbox"/>
7.13	(L1) Ensure mobile devices require the use of a password (Scored)	<input type="checkbox"/>	<input type="checkbox"/>

Appendix: Change History

Date	Version	Changes for this version
12/19/18	1.0.0	Initial Release